

Number of contacts

10 +



Inserts

| Identification | Series | Part No. | | Drawing | Dimensions in mm |
|---|--------|-----------------------|-----------------------|---------|------------------|
| | | Male insert (M) | Female insert (F) | | |
| <p>Screw terminal</p> | Han A® | 09 20 010 2612 | 09 20 010 2812 | | Screw terminal |
| <p>Crimp terminal Order crimp contacts separately</p> | Han A® | 09 20 010 3001 | 09 20 010 3101 | | Crimp terminal |

1) Distance for contact max. 24 mm

View from termination side

| | |
|---|---|
| | |
| M | F |

Panel cut out for inserts for use without hoods/housings

| Identification | Wire gauge (mm ²) | Part No. | | Drawing | Dimensions in mm |
|--|--|---|---|---------|------------------|
| | | Male contacts | Female contacts | | |
| <p>Crimp contacts</p> <p>Power contacts</p> <p>silver plated</p> | 0.5 0.75 1.0 1.5 2.5 3 4 | 09 33 000 6121 09 33 000 6114 09 33 000 6105 09 33 000 6104 09 33 000 6102 09 33 000 6106 09 33 000 6107 | 09 33 000 6220 09 33 000 6214 09 33 000 6205 09 33 000 6204 09 33 000 6202 09 33 000 6206 09 33 000 6207 | | |
| <p>gold plated</p> | 0.5 0.75 1.0 1.5 2.5 4.0 | 09 33 000 6122 09 33 000 6115 09 33 000 6118 09 33 000 6116 09 33 000 6123 09 33 000 6119 | 09 33 000 6222 09 33 000 6215 09 33 000 6218 09 33 000 6216 09 33 000 6223 09 33 000 6221 | | |

Crimp contact identification

| Identification | Wire gauge | AWG | Stripping length |
|----------------|----------------------|--------|------------------|
| no groove | 0.5 mm ² | AWG 20 | 7.5 mm |
| 1 groove* | 0.75 mm ² | AWG 18 | 7.5 mm |
| 1 groove | 1 mm ² | AWG 18 | 7.5 mm |
| 2 grooves | 1.5 mm ² | AWG 16 | 7.5 mm |
| 3 grooves | 2.5 mm ² | AWG 14 | 7.5 mm |
| wide groove | 3.0 mm ² | AWG 12 | 7.5 mm |
| no groove | 4 mm ² | AWG 12 | 7.5 mm |

* on the back crimp collar