

Number of contacts

6 +



Inserts

Han E / EE

Identification	Series	Part No.		Drawing	Dimensions in mm																				
		Male insert (M)	Female insert (F)																						
Screw terminal with wire protection 	Han E®	09 33 006 2601	09 33 006 2701	<table border="1"> <tr> <td></td> <td>a</td> <td>b</td> <td>c</td> <td>d</td> </tr> <tr> <td>Han E® screw</td> <td>18</td> <td>33</td> <td>18</td> <td>35</td> </tr> <tr> <td>Han® ES / Han E® crimp</td> <td>19</td> <td>34</td> <td>19</td> <td>36</td> </tr> <tr> <td>Han ESS</td> <td>34</td> <td>49</td> <td>32</td> <td>49</td> </tr> </table> <p>1) Distance for contact max. 21 mm</p>		a	b	c	d	Han E® screw	18	33	18	35	Han® ES / Han E® crimp	19	34	19	36	Han ESS	34	49	32	49	<p>View from termination side</p> <p>M: 4 ● 1, 5 ● 2, 6 ● 3</p> <p>F: 1 ● 4, 2 ● 5, 3 ● 6</p>
	a	b	c		d																				
Han E® screw	18	33	18		35																				
Han® ES / Han E® crimp	19	34	19		36																				
Han ESS	34	49	32		49																				
Cage-clamp terminal 	Han® ES	09 33 006 2616	09 33 006 2716																						
Cage-clamp terminal two terminals per contact 	Han® ESS	09 33 006 2672	09 33 006 2772																						
Crimp terminal Order contacts separately 	Han E®	09 33 006 2602	09 33 006 2702																						
		<p>Panel cut out for inserts for use without hoods/housings</p>																							

Identification	Wire gauge (mm²)	Part No.		Drawing	Dimensions in mm																																				
		Male contacts	Female contacts																																						
Crimp contacts Power contacts silver plated 	0.14-0.37 0.5 0.75 1.0 1.5 2.5 3 4	09 33 000 6127* 09 33 000 6121 09 33 000 6114 09 33 000 6105 09 33 000 6104 09 33 000 6102 09 33 000 6106 09 33 000 6107	09 33 000 6227* 09 33 000 6220 09 33 000 6214 09 33 000 6205 09 33 000 6204 09 33 000 6202 09 33 000 6206 09 33 000 6207		Operating contact Identification Relay contact																																				
gold plated 	0.14-0.37 0.5 0.75 1.0 1.5 2.5 4.0	09 33 000 6117* 09 33 000 6122 09 33 000 6115 09 33 000 6118 09 33 000 6116 09 33 000 6123 09 33 000 6119	09 33 000 6217* 09 33 000 6222 09 33 000 6215 09 33 000 6218 09 33 000 6216 09 33 000 6223 09 33 000 6221																																						
Relay contact silver plated 	0.75-1 1.5 2.5	09 33 000 6109 09 33 000 6110 09 33 000 6111		Crimp contact identification <table border="1"> <thead> <tr> <th>Identification</th> <th>Wire gauge</th> <th>AWG</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>no groove</td> <td>0.14-0.37 mm²</td> <td>AWG 26-22</td> <td>7,5 mm</td> </tr> <tr> <td>no groove</td> <td>0.5 mm²</td> <td>AWG 20</td> <td>7,5 mm</td> </tr> <tr> <td>1 groove*</td> <td>0.75 mm²</td> <td>AWG 18</td> <td>7,5 mm</td> </tr> <tr> <td>1 groove</td> <td>1 mm²</td> <td>AWG 18</td> <td>7,5 mm</td> </tr> <tr> <td>2 grooves</td> <td>1.5 mm²</td> <td>AWG 16</td> <td>7,5 mm</td> </tr> <tr> <td>3 grooves</td> <td>2.5 mm²</td> <td>AWG 14</td> <td>7,5 mm</td> </tr> <tr> <td>wide groove</td> <td>3.0 mm²</td> <td>AWG 12</td> <td>7,5 mm</td> </tr> <tr> <td>no groove</td> <td>4 mm²</td> <td>AWG 12</td> <td>7,5 mm</td> </tr> </tbody> </table>		Identification	Wire gauge	AWG	Stripping length	no groove	0.14-0.37 mm²	AWG 26-22	7,5 mm	no groove	0.5 mm²	AWG 20	7,5 mm	1 groove*	0.75 mm²	AWG 18	7,5 mm	1 groove	1 mm²	AWG 18	7,5 mm	2 grooves	1.5 mm²	AWG 16	7,5 mm	3 grooves	2.5 mm²	AWG 14	7,5 mm	wide groove	3.0 mm²	AWG 12	7,5 mm	no groove	4 mm²	AWG 12	7,5 mm
Identification	Wire gauge	AWG	Stripping length																																						
no groove	0.14-0.37 mm²	AWG 26-22	7,5 mm																																						
no groove	0.5 mm²	AWG 20	7,5 mm																																						
1 groove*	0.75 mm²	AWG 18	7,5 mm																																						
1 groove	1 mm²	AWG 18	7,5 mm																																						
2 grooves	1.5 mm²	AWG 16	7,5 mm																																						
3 grooves	2.5 mm²	AWG 14	7,5 mm																																						
wide groove	3.0 mm²	AWG 12	7,5 mm																																						
no groove	4 mm²	AWG 12	7,5 mm																																						

Coding Pin 		09 33 000 9954	Use of the coding pin prevents incorrect mating to other connectors of the same type. The male pin should be omitted from the opposing cavity in the male insert.
----------------	--	-----------------------	--

* only to be used with BUCHANAN crimping tool 09 99 000 0001 and adjustment gauge 09 99 000 0203

Stock items in bold type