

Number of contacts

7 +



Inserts

Han D/DD

Identification	Series	Part No.		Drawing	Dimensions in mm
		Male insert (M)	Female insert (F)		
<p>Crimp terminal Order crimp contacts separately</p>	Han D®	09 21 007 3031¹⁾	09 21 007 3131¹⁾		<p>Contact arrangement View from termination side</p>
<p>¹⁾ Attention Only for thermoplastic hoods/housings</p>					
<p>Coding system with loss of contact</p>		09 33 000 9915	<p>Use of the coding pin prevents incorrect mating to other connectors of the same type.</p> <p>The male pin should be omitted from the opposing cavity in the male insert.</p>		

Identification	Wire gauge (mm ²)	Part No.		Drawing	Dimensions in mm
		Male contacts	Female contacts		
<p>Crimp contacts</p>					
<p>silver plated</p>	<p>0.14-0.37 0.5 0.75 1.0 1.5 2.5</p>	<p>09 15 000 6104 09 15 000 6103 09 15 000 6105 09 15 000 6102 09 15 000 6101 09 15 000 6106</p>	<p>09 15 000 6204 09 15 000 6203 09 15 000 6205 09 15 000 6202 09 15 000 6201 09 15 000 6206</p>		
<p>gold plated</p>	<p>0.14-0.37 0.5 0.75 1.0 1.5 2.5</p>	<p>09 15 000 6124 09 15 000 6123 09 15 000 6125 09 15 000 6122 09 15 000 6121 09 15 000 6126</p>	<p>09 15 000 6224 09 15 000 6223 09 15 000 6225 09 15 000 6222 09 15 000 6221 09 15 000 6226</p>		
<p>FOC contacts for 1 mm plastic fibre</p>		20 10 001 3212	20 10 001 3222		

Wire gauge	ø	Stripping length
0.14-0.37 mm ²	AWG 26-22	0.90 mm
0.5 mm ²	AWG 20	1.10 mm
0.75 mm ²	AWG 18	1.30 mm
1 mm ²	AWG 18	1.45 mm
1.5 mm ²	AWG 16	1.75 mm
2.5 mm ²	AWG 14	2.25 mm

Stock items in bold type