

Number of contacts

7 +



Inserts

Han D/DD

Identification	Series	Part No.		Drawing	Dimensions in mm
		Male insert (M)	Female insert (F)		
<p><b>Crimp terminal</b> Order crimp contacts separately</p>	Han D®	<b>09 21 007 3031<sup>1)</sup></b>	<b>09 21 007 3131<sup>1)</sup></b>		<p><b>Contact arrangement</b> View from termination side</p>
<p><sup>1)</sup> Attention Only for thermoplastic hoods/housings</p>					
<p><b>Coding system with loss of contact</b></p>		<b>09 33 000 9915</b>	<p>Use of the coding pin prevents incorrect mating to other connectors of the same type.</p> <p>The male pin should be omitted from the opposing cavity in the male insert.</p>		

Identification	Wire gauge (mm <sup>2</sup> )	Part No.		Drawing	Dimensions in mm
		Male contacts	Female contacts		
<p><b>Crimp contacts</b></p>					
<p>silver plated</p>	<p>0.14-0.37 0.5 0.75 1.0 1.5 2.5</p>	<p><b>09 15 000 6104</b> <b>09 15 000 6103</b> <b>09 15 000 6105</b> <b>09 15 000 6102</b> <b>09 15 000 6101</b> <b>09 15 000 6106</b></p>	<p><b>09 15 000 6204</b> <b>09 15 000 6203</b> <b>09 15 000 6205</b> <b>09 15 000 6202</b> <b>09 15 000 6201</b> <b>09 15 000 6206</b></p>		
<p>gold plated</p>	<p>0.14-0.37 0.5 0.75 1.0 1.5 2.5</p>	<p><b>09 15 000 6124</b> <b>09 15 000 6123</b> <b>09 15 000 6125</b> <b>09 15 000 6122</b> <b>09 15 000 6121</b> <b>09 15 000 6126</b></p>	<p><b>09 15 000 6224</b> <b>09 15 000 6223</b> <b>09 15 000 6225</b> <b>09 15 000 6222</b> <b>09 15 000 6221</b> <b>09 15 000 6226</b></p>		
<p><b>FOC contacts for 1 mm plastic fibre</b></p>		<b>20 10 001 3212</b>	<b>20 10 001 3222</b>		

Wire gauge	ø	Stripping length
0.14-0.37 mm <sup>2</sup>	AWG 26-22	0.90 mm
0.5 mm <sup>2</sup>	AWG 20	1.10 mm
0.75 mm <sup>2</sup>	AWG 18	1.30 mm
1 mm <sup>2</sup>	AWG 18	1.45 mm
1.5 mm <sup>2</sup>	AWG 16	1.75 mm
2.5 mm <sup>2</sup>	AWG 14	2.25 mm

Stock items in bold type