






Number of contacts




25+



Han
D/DD

Inserts

Identification	Series	Part No.		Drawing	Dimensions in mm
		Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately 	Han D [®]	09 21 025 3001	09 21 025 3101	 <p>1) Distance for contact max. 24 mm</p> <p>Contact arrangement View from termination side</p> 	
Wrap terminal 1 x 1 mm 	Han D [®]	09 21 025 2601	09 21 025 2701	<p>Panel cut out for inserts for use without hoods/housings</p> 	

Identification	Wire gauge (mm ²)	Part No.		Drawing	Dimensions in mm																					
		Male contacts	Female contacts																							
Crimp contacts silver plated  gold plated 	0.14-0.37 0.5 0.75 1.0 1.5 2.5 0.14-0.37 0.5 0.75 1.0 1.5 2.5	09 15 000 6104 09 15 000 6103 09 15 000 6105 09 15 000 6102 09 15 000 6101 09 15 000 6106 09 15 000 6124 09 15 000 6123 09 15 000 6125 09 15 000 6122 09 15 000 6121 09 15 000 6126	09 15 000 6204 09 15 000 6203 09 15 000 6205 09 15 000 6202 09 15 000 6201 09 15 000 6206 09 15 000 6224 09 15 000 6223 09 15 000 6225 09 15 000 6222 09 15 000 6221 09 15 000 6226		<table border="1"> <thead> <tr> <th>Wire gauge</th> <th>ø</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>0.14-0.37 mm²</td> <td>AWG 26-22</td> <td>0.90 mm</td> </tr> <tr> <td>0.5 mm²</td> <td>AWG 20</td> <td>1.10 mm</td> </tr> <tr> <td>0.75 mm²</td> <td>AWG 18</td> <td>1.30 mm</td> </tr> <tr> <td>1 mm²</td> <td>AWG 18</td> <td>1.45 mm</td> </tr> <tr> <td>1.5 mm²</td> <td>AWG 16</td> <td>1.75 mm</td> </tr> <tr> <td>2.5 mm²</td> <td>AWG 14</td> <td>2.25 mm</td> </tr> </tbody> </table>	Wire gauge	ø	Stripping length	0.14-0.37 mm ²	AWG 26-22	0.90 mm	0.5 mm ²	AWG 20	1.10 mm	0.75 mm ²	AWG 18	1.30 mm	1 mm ²	AWG 18	1.45 mm	1.5 mm ²	AWG 16	1.75 mm	2.5 mm ²	AWG 14	2.25 mm
Wire gauge	ø	Stripping length																								
0.14-0.37 mm ²	AWG 26-22	0.90 mm																								
0.5 mm ²	AWG 20	1.10 mm																								
0.75 mm ²	AWG 18	1.30 mm																								
1 mm ²	AWG 18	1.45 mm																								
1.5 mm ²	AWG 16	1.75 mm																								
2.5 mm ²	AWG 14	2.25 mm																								
FOC contacts for 1 mm plastic fibre		20 10 001 3213	20 10 001 3222	