



RC UNIT FOR MCB 5SY TYPE A (PSE/SSF),
T=70MM 0.3-40A 2POLE IFN 0,3A 230V

Similar to image

Technical data:

mounting position		any
Height	mm	90
Width	mm	71
Depth	mm	70
Design of the product		Instantaneous
Supply voltage / for AC / rated value	V	400
Resistance against the impulse current / rated value	kA	1
Ambient temperature	°C	-25 ... +45
Ambient temperature • during storage	°C	-40 ... +75
Mechanical operating cycles as operating time / typical		10,000
Overvoltage class		III
Supply voltage / for testing equipment / minimum	V	195
Protection against electrical shock		Finger and back-of-hand safe
Position / of power supply cord		top or bottom
Tightening torque • with screw-type terminals	N·m	2.5 ... 3
Section de conducteur raccordable		

<ul style="list-style-type: none"> • solid 	mm ²	1.5 ... 25
<ul style="list-style-type: none"> • multibrin 	mm ²	1.5 ... 25
Product feature <ul style="list-style-type: none"> • silicon-free • halogen-free 		Yes Yes
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30		28
Item designation <ul style="list-style-type: none"> • according to DIN EN 61346-2 • according to DIN EN 81346-2 		F F

Certificates/approvals:

General Product Approval	Declaration of Conformity	other
		
		Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)



<http://support.automation.siemens.com/WW/view/en/5SM2622-6/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM2622-6

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Mar 3, 2014