

Product data sheet

Item No. 92.232.3000.1

Cable assembly GST18I3K1BS 15 30SW

geis® Extension cable female - male; length: 3m; type GST18I3;
3-pole; 250 V / 16 A; colour of coding: black with black strain-relief;
cable: H05VV-F 3G1,5, colour: black



Item No.	92.232.3000.1
EAN	4015573326705
Order Unit	25 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Female - male
Type of cord set	Connecting cable



Version cable end 1	GST18i3 female
Version cable end 2	GST18i3 plug

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	3 m
--------------	-----

Technical drawing

Buchenteil/female connector Steckerteil/male connector

Gesamtlänge / total length $L \pm 3\%$

Kabel/cable H05VV-F3G1,5
Farbe/colour: siehe Tabelle/see table

.F	Farbe colour	Codierung Buchse female *X*	Codierung Stecker male *Y*	Kabelfarbe cable colour
.1	schwarz black	N ⊕ L	L ⊕ N	schwarz black
.2	weiß white	N ⊕ L	L ⊕ N	weiß white
.3	grau grey	N ⊕ L	L ⊕ N	schwarz black
.5	rot red	N ⊕ L	L ⊕ N	schwarz black

Typ/type: GST1813K1BS 15 .. SW = schwarz/black
WS = weiß/white
GRO1 = grau/grey
RT03 = rot/red

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) exampel (colour: black)	Typ type
92.232.XX00.F	XX in dm-Schritten	92.232.1000.1 = 10dm/L= 1000mm	GST1813K1BS 15 10SW
U2.232.XX00.F	XX in m-Schritten	U2.232.1200.1 = 12 m/L=12000mm	GST1813K1BS 15 X12SW
92.232.XX90.F	XX in dm-Schritten	92.232.1090.1 = 10dm/L= 1000mm	

90.F = spezielle Verpackung und Etikettierung nach A 1960.000
special packaging and lable according to A 1960.000

Furthering Size ISO 14200(1) Telecommunications system size ISO 14200(1) ...
This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.
Conformity with Wieland document 00-TDM-05/03 (list of prohibited / declare hazardous substances) to be declared

First tolerance mark: - GD - Zeichnung, keine rechnerischen Änderungen
GD - drawing, no manual modifications allowed

General tolerance: - T - Zeichnung, keine rechnerischen Änderungen
T - drawing, no manual modifications allowed

Material: Werkstoff/Material: 2.006
Drawing date: 20.01.2017
Drawing name: 01Stück 1.
Drawing No./Drawing No.: 92.232.0200.1 01K a

Wieland logo

PRE-ASSEMBLED CABLE
KONFEKT_LEITUNG
Buchse/female - Stecker/male 1,5gmm
Cr impausführung/crimpersion: KT 250V

Weitere Daten siehe Katalog
further data see catalog