



Interrupteur général



Powering Business Worldwide™

Référence
Code

IS-40/2
276271

Technische Daten nach ETIM 4.0

Mounting type			DIN-rail
Frequency		Hz	60 Hz
Rated current		A	40 A
Rated voltage		V	240 V
Release characteristic			-
Rated insulation voltage Ui		V	690 V
Number of poles			2
Rated switching capacity		kA	0 kA
Construction size (in accordance with DIN 43880)			2
Over voltage category			0
Pollution degree			3
Rated surge voltage invariability		kV	6 kV
Degree of protection (IP)			IP40
Concurrently switching N-neutral			false
Type de tension			AC
Fonction			-
Avec lampe-témoin			No
Profondeur de montage		mm	69.5
Courant assigné d'emploi		A	40
Tension assignée d'emploi		V	240
Puissance lampe max.		W	0
Nombre de contacts à fermeture			0
Nombre de contacts à ouverture			0
Nombre de contacts inverseurs			0
Voyants lumineux			not applicable
Tenue aux courts-circuits (Icw)		kA	2
Pouvoir assigné de coupure		kA	0
Largeur en nombres de modules			2
Couleur de la verrine			not applicable
Culot de lampe			not applicable
Tension assignée minimale		V	240
Ouverture positive (selon DIN VDE 0113)			No
Degré de protection (IP)			IP40