

# Miniature Power Relays MY(S)

## MY(S) Versatile plug-in Relay



- Reduces wiring work by 60% when combined with the PYF-PU Push-In Plus Socket (according to actual OMRON measurements).
- 10 A (DPDT) and 5 A (4PDT)
- Gold-clad contacts (MY4(S))
- Test button (lockable)
- Wide portfolio includes hermetically sealed and latching types
- 2.6 mm wide pins offer higher conductivity and less temperature increase



The compliant standards depend on the model.  
For details, refer to information provided for individual models.

Refer to the Common Relay Precautions and Safety Precautions on page 34.

## Model Number Structure

| Coil Polarity (DC case) * | Type                          | Contact form               | Plug-In socket/solder terminals |   |                       | Flange mounting |     |
|---------------------------|-------------------------------|----------------------------|---------------------------------|---|-----------------------|-----------------|-----|
|                           |                               |                            | With LED indicator              | With LED Indicator and Lockable test button | Without LED Indicator |                 |     |
|                           | Standard model                | DPDT                       | MY2N(S)                         | MY2IN(S)                                    | MY2(S)                | MY2F            |     |
|                           |                               | DPDT (Bifurcated)          | MY2ZN                           | ---   | ---                   | ---             |     |
|                           |                               | 4PDT                       | MY4N(S)                         | MY4IN(S)                                    | MY4(S)                | MY4F            |     |
|                           |                               | 4PDT (Bifurcated)          | MY4ZN(S)                        | MY4ZIN(S)                                   | MY4Z(S)               | MY4ZF           |     |
|                           | With Built-in diode (DC only) |                            | DPDT                            | MY2N-D2(S)                                  | MY2IN-D2(S)           | ---             | --- |
|                           |                               |                            | DPDT (Bifurcated)               | MY2ZN-D2                                    | ---                   | ---             | --- |
|                           |                               |                            | 4PDT                            | MY4N-D2(S)                                  | MY4IN-D2(S)           | ---             | --- |
|                           |                               |                            | 4PDT (Bifurcated)               | MY4ZN-D2(S)                                 | MY4ZIN-D2(S)          | ---             | --- |
|                           | With Built-in CR (AC only)    |                            | DPDT                            | MY2N-CR(S)                                  | MY2IN-CR(S)           | ---             | --- |
|                           |                               |                            | 4PDT                            | MY4N-CR(S)                                  | MY4IN-CR(S)           | ---             | --- |
|                           |                               |                            | 4PDT (Bifurcated)               | MY4ZN-CR(S)                                 | MY4ZIN-CR(S)          | ---             | --- |
|                           | High reliability contacts     | 4PDT (Crossbar Bifurcated) | ---                             | ---   | MY4Z-CBG              | ---             |     |
|                           | Plastic Sealed                | 4PDT                       | MYQ4N                           | ---   | ---                   | ---             |     |
|                           |                               | 4PDT (Bifurcated)          | ---                             | ---   | MYQ4Z                 | ---             |     |
| Latching (coil latching)  | DPDT                          | ---                        | ---                             | MY2K-US                                     | ---                   |                 |     |
| Hermetic                  | 4PDT                          | ---                        | ---                             | MY4H  | ---                   |                 |     |
|                           | 4PDT (Bifurcated)             | ---                        | ---                             | MY4ZH                                       | ---                   |                 |     |
|                           | Standard model                | DPDT                       | MY2N1(S)                        | MY2IN1(S)                                   | ---                   | ---             |     |
|                           |                               | 4PDT                       | MY4N1(S)                        | MY4IN1(S)                                   | ---                   | ---             |     |
|                           |                               | 4PDT (Bifurcated)          | MY4ZN1(S)                       | MY4ZIN1(S)                                  | ---                   | ---             |     |
|                           | With Built-in diode (DC only) |                            | DPDT                            | MY2N1-D2(S)                                 | MY2IN1-D2(S)          | ---             | --- |
|                           |                               |                            | 4PDT                            | MY4N1-D2(S)                                 | MY4IN1-D2(S)          | ---             | --- |
|                           |                               |                            | 4PDT (Bifurcated)               | MY4ZN1-D2(S)                                | MY4ZIN1-D2(S)         | ---             | --- |

\* In case of AC coil type relay, please select them from "Type 1" of Coil Polarity.

Refer to *Connection Socket and Mounting Bracket Selection Table* on page 25 in *Options* for information on the possible combinations of Models with Plug-in Terminals and Sockets.

# MY(S)

## Contents

|   |    |
|---|----|
| Model Number Structure.....   | 1  |
| Specifications  |    |
| Coil Ratings .....  | 2  |
| MY2(S)/MY4(S)/MY4Z(S).....  | 3  |
| Engineering Data .....  | 6  |
| Detailed Information on Models Certified for Safety Standards, MY2(S)/MY4(S)/MY4Z(S)..... | 8  |
| Models Other Than MY(S) Models  |    |
| MY2ZN .....   | 9  |
| MY□F .....  | 11 |
| Detailed Information on Models Certified for Safety Standards, MY2ZN and MY□F.....        | 14 |
| MY4Z-CBG .....  | 15 |
| MYQ4 .....  | 17 |
| MY2K .....  | 19 |
| MY4(Z)H.....  | 21 |
| Socket for MY.....  | 23 |
| Options.....  | 25 |
| Safety Precautions .....  | 34 |

## Specifications

### Coil Ratings

#### MY(S)

| Rated voltage | Rated current |              | Coil resistance | Coil inductance (reference value) |         | Must operate voltage | Must release voltage | Max. voltage | Power consumption (approx.)   |
|---------------|---------------|--------------|-----------------|-----------------------------------|---------|----------------------|----------------------|--------------|-------------------------------|
|               | 50 Hz         | 60 Hz        |                 | Arm. OFF                          | Arm. ON |                      |                      |              |                               |
| AC            | 6 V           | 214.1 mA     | 183 mA          | 12.2 Ω                            | 0.04 H  | 80% max.             | 30% min.             | 110%         | Approx. 0.9 to 1.3 VA (60 Hz) |
|               | 12 V          | 106.5 mA     | 91 mA           | 46 Ω                              | 0.17 H  |                      |                      |              |                               |
|               | 24 V          | 53.8 mA      | 46 mA           | 180 Ω                             | 0.69 H  |                      |                      |              |                               |
|               | 48/50 V       | 24.7/25.7 mA | 21.1/22.0 mA    | 788 Ω                             | 3.22 H  |                      |                      |              |                               |
|               | 110/120 V     | 9.9/10.8 mA  | 8.4/9.2 mA      | 4,430 Ω                           | 19.20 H |                      |                      |              |                               |
|               | 220/240 V     | 4.8/5.3 mA   | 4.2/4.6 mA      | 18,790 Ω                          | 83.50 H |                      |                      |              |                               |
| DC            | 6 V           | 151 mA       |                 | 39.8 Ω                            | 0.17 H  | 80% max.             | 10% min.             | 110%         | 0.9 W                         |
|               | 12 V          | 75 mA        |                 | 160 Ω                             | 0.73 H  |                      |                      |              |                               |
|               | 24 V          | 37.7 mA      |                 | 636 Ω                             | 3.20 H  |                      |                      |              |                               |
|               | 48 V          | 18.8 mA      |                 | 2,560 Ω                           | 10.60 H |                      |                      |              |                               |
|               | 100/110 V     | 9.0/9.9 mA   |                 | 11,100 Ω                          | 45.60 H |                      |                      |              |                               |

- Note:** 1. The rated current and coil resistance are measured at a coil temperature of 23°C with tolerances of +15%/–20% for rated currents and ±15% for DC coil resistance.  
 2. Performance characteristic data are measured at a coil temperature of 23°C.  
 3. AC coil resistance and impedance are provided as reference values (at 60 Hz).  
 4. Power consumption drop was measured for the above data. When driving transistors, check leakage current and connect a bleeder resistor if required.

#### MY2ZN, MY□F, MY4(Z)H

| Rated voltage (V) | Item    | Rated current (mA) |         | Coil resistance (Ω) | Coil inductance (H) |             | Must-operate voltage (V) | Must-release voltage (V) | Maximum voltage (V)   | Power consumption (VA, W)     |
|-------------------|---------|--------------------|---------|---------------------|---------------------|-------------|--------------------------|--------------------------|-----------------------|-------------------------------|
|                   |         | 50 Hz              | 60 Hz   |                     | Armature OFF        | Armature ON |                          |                          |                       |                               |
| AC                | 12      | 106.5              | 91      | 46                  | 0.17                | 0.33        | 80% max.*1               | 30% min.*2               | 110% of rated voltage | Approx. 0.9 to 1.3 VA (60 Hz) |
|                   | 24      | 53.8               | 46      | 180                 | 0.69                | 1.3         |                          |                          |                       |                               |
|                   | 100/110 | 11.7/12.9          | 10/11   | 3,750               | 14.54               | 24.6        |                          |                          |                       |                               |
|                   | 110/120 | 9.9/10.8           | 8.4/9.2 | 4,430               | 19.2                | 32.1        |                          |                          |                       |                               |
|                   | 200/220 | 6.2/6.8            | 5.3/5.8 | 12,950              | 54.75               | 94.07       |                          |                          |                       |                               |
|                   | 220/240 | 4.8/5.3            | 4.2/4.6 | 18,790              | 83.5                | 136.4       |                          |                          |                       |                               |
| DC                | 12      | 75                 |         | 160                 | 0.73                | 1.37        | 80% max.*1               | 10% min.*2               | 110% of rated voltage | Approx. 0.9                   |
|                   | 24      | 36.9               |         | 650                 | 3.2                 | 5.72        |                          |                          |                       |                               |
|                   | 48      | 18.5               |         | 2,600               | 10.6                | 21.0        |                          |                          |                       |                               |
|                   | 100/110 | 9.1/10             |         | 11,000              | 45.6                | 86.2        |                          |                          |                       |                               |

- Note:** 1. The rated current and coil resistance are measured at a coil temperature of 23°C with tolerances of +15%/–20% for the AC rated current and ±15% for the DC coil resistance.  
 2. The AC coil resistance and inductance values are reference values only (at 60 Hz).  
 3. Operating characteristics were measured at a coil temperature of 23°C.  
 4. The maximum voltage capacity was measured at an ambient temperature of 23°C.  
 \*1. There is variation between products, but actual values are 80% max. To ensure operation, apply at least 80% of the rated value.  
 \*2. There is variation between products, but actual values are 30% minimum for AC and 10% minimum for DC. To ensure release, use a value that is lower than the specified value.  
**Note:** Refer to page 19 for the coil specifications of the MY2K.

# Miniature Power Relays: MY2(S)/MY4(S)/MY4Z(S)



Refer to the standards certifications and compliance section of your OMRON website for the latest information on certified models.

## Specifications

### Contact Ratings

| Item                           | DPDT                          |   | 4PDT                          |   | 4PDT (bifurcated)             |   |
|--------------------------------|-------------------------------|---|-------------------------------|---|-------------------------------|---|
|                                | Resistive load<br>(cos φ = 1) | Inductive load<br>(cos φ = 0.4, L/R = 7 ms) | Resistive load<br>(cos φ = 1) | Inductive load<br>(cos φ = 0.4, L/R = 7 ms) | Resistive load<br>(cos φ = 1) | Inductive load<br>(cos φ = 0.4, L/R = 7 ms) |
| Rated load                     | 5A, 250 VAC<br>5A, 30 VDC     | 2A, 250 VAC<br>2A, 30 VDC                   | 3 A, 250 VAC<br>3 A, 30 VDC   | 0.8 A, 250 VAC<br>1.5 A, 30 VDC             | 3 A, 250 VAC<br>3 A, 30 VDC   | 0.8 A, 250 VAC<br>1.5 A, 30 VDC             |
| Carry current                  | 10 A (see note)               |   | 5 A (see note)                |   |                               |   |
| Max. switching voltage         | 250 VAC<br>125 VDC            |   |                               |   |                               |   |
| Max. switching current         | 10 A                          |   | 5 A                           |   |                               |   |
| Contact materials              | Ag                            |   | Au cladding + Ag alloy        |   |                               |   |
| Failure rate (reference value) | 5 VDC, 1 mA                   |   | 1 VDC, 1 mA                   |   | 1 VDC, 100 μA                 |   |

Note: Don't exceed the carry current of a Socket in use. Please see page 23.

### Characteristics

| Item                     | All Relays   |
|--------------------------|--|
| Contact resistance       | 100 mΩ max. (50 mΩ: 4PDT bifurcated)   |
| Operate time             | 20 ms max.   |
| Release time             | 20 ms max.   |
| Max. operating frequency | Mechanical:18,000 operations/hr<br>Electrical:1,800 operations/hr (under rated load)   |
| Insulation resistance    | 100 MΩ min. (at 500 VDC)   |
| Dielectric strength      | 2,000 VAC, 50/60 Hz for 1.0 min (1,000 VAC between contacts of same polarity)  |
| Vibration resistance     | Destruction:10 to 55 to 10 Hz, 0.5 mm single amplitude (1.0 mm double amplitude)<br>Malfunction:10 to 55 to 10 Hz, 0.5 mm single amplitude (1.0 mm double amplitude) |
| Shock resistance         | Destruction:1,000 m/s <sup>2</sup><br>Malfunction:200 m/s <sup>2</sup>   |
| Endurance                | See the following table.   |
| Ambient temperature      | Operating: -55 to 70°C (with no icing)   |
| Ambient humidity         | Operating: 5 to 85% RH   |
| Weight                   | Approx. 35 g   |

Note: The values given above are initial values.

### Endurance Characteristics

| Contact form      | Mechanical life (at 18,000 operations/hr)                       | Electrical life (at 1,800 operations/hr under rated load) |
|-------------------|---|---|
| DPDT              | AC:50,000,000 operations min.<br>DC:100,000,000 operations min. | 500,000 operations min.                                   |
| 4PDT              |   | 200,000 operations min.                                   |
| 4PDT (bifurcated) | 20,000,000 operations min.                                      | 100,000 operations min.                                   |


# MY(S)

## Dimensions

(Unit: mm)

### List of Models


MY2□□(S) Series




Note: The picture is lockable test button type.

#### Terminal Arrangement/Internal Connections (Bottom View)


**MY2IN(S)**  
(AC Model)




**MY2IN(S)**  
(DC Models)




**MY2IN-D2(S)**  
(DC Models Only)




**MY2IN-CR**  
(AC Models Only)




**MY2IN1(S)**  
(DC Models)



**MY2IN1-D2(S)**  
(DC Models Only)




MY4□□(S) series




Note: The picture is lockable test button type.

Terminal Arrangement/Internal Connections (Bottom View)


MY4(Z)IN(S)  
(DC Models)




MY4(Z)IN(S)  
(AC Models)




MY4(Z)IN-D2(S)  
(DC Models Only)




MY4(Z)IN-CR(S)  
(AC Models Only)



MY4(Z)IN1(S)  
(DC Models)




MY4(Z)IN1-D2(S)  
(DC Models Only)




# MY(S)

## Engineering Data MY2(S)/ MY4(S)/MY4Z(S)


### Maximum Switching Capacity MY2(S)




### MY4(S) and MY4Z(S)




### Endurance Curve MY2(S)




### MY2(S)




### MY4(S)




### MY4(S)




### MY4Z(S)



### MY4Z(S)



### Common Specifications for MY2(S)/MY4(S)/MY4Z(S) Malfunctioning Shock




N = 20

Measurement: Shock was applied 3 times each in 6 directions along 3 axes with the Relay energized and not energized to check the shock values that cause the Relay to malfunction.


Criteria: Non-energized: 200 m/s<sup>2</sup>,  
Energized: 200 m/s<sup>2</sup>

#### Shock direction




# Engineering Data MY(S) (MY2ZN, MY□F)


## Ambient Temperature vs. Must-operate and Must-release Voltage MY2 AC Models




## MY2 DC Models



## MY4 AC Models




## MY4 DC Models




## Ambient Temperature vs. Coil Temperature Rise


### MY2 AC Models, 50 Hz




### MY2 DC Models



### MY4 AC Models, 50 Hz




### MY4 DC Models




## Models with built-in diodes

The diode absorbs surge from the coil. This type is best suited for applications with semiconductor circuits.

### With Diode




### Without Diode




- Note:**
1. Make sure that the polarity is correct.
  2. The release time will increase, but the 20-ms specification for standard models is satisfied.
  3. Diode properties: The diode has a reversed dielectric strength of 1,000 V. Forward current: 1 A

## Models with Built-in CR Circuits

### With CR



### Without CR



# MY(S)

## Detailed Information on Models Certified for Safety Standards, MY2(S)/MY4(S)/MY4Z(S)

### VDE-certified Models (No. 112467UG, EN61810-1)

| Model | Coil ratings  | Contact form | Contact ratings  | File No.       | Certified number of operations  |
|-------|---|--------------|--|----------------|---|
| MY□   | 6, 12, 24, 48/50, 100/<br>110, 110/120, 200/<br>220, and 220/240 VAC<br>6, 12, 24, 48, 100/<br>110, and 125 VDC | DPDT         | 10 A, 250 VAC (cos φ = 1)<br>10 A, 30 VDC (L/R = 0 ms) | 6692 (VDE0435) | MY2: 10,000 operations<br>MY4: 100,000 operations<br>MY4Z: 50,000 operations (AC) |
|       |   | 4PDT         | 5 A, 250 VAC (cos φ = 1)<br>5 A, 30 VDC (L/R = 0 ms)   |                |   |

### UL508-certified Models (File No. 41515)

| Model | Coil ratings                 | Contact form | Contact ratings                           | File No.       | Certified number of operations |
|-------|------------------------------|--------------|---|----------------|--------------------------------|
| MY□   | 6 to 240 VAC<br>6 to 125 VDC | DPDT         | 10A, 250 VAC (General Use)                | E41515 (UL508) | 6,000                          |
|       |                              |              | 10A, 30 VDC (General Use)                 |                |                                |
|       |                              |              | 7A, 240 VAC (General Use)                 |                |                                |
|       |                              |              | 7A, 24 VDC (Resistive)                    |                |                                |
|       |                              |              | 5A, 240 VAC (General Use)                 |                |                                |
|       |                              |              | 5A, 250 VAC (Resistive)                   |                |                                |
|       |                              |              | 5A, 30 VDC (Resistive)                    |                |                                |
|       |                              |              | 3A, 265 VAC (Resistive)                   |                |                                |
|       |                              |              | 1/6HP, 250 VAC                            |                |                                |
|       |                              |              | 1/8HP, 265 VAC                            |                |                                |
|       |                              |              | 1/10HP, 120 VAC                           |                |                                |
|       |                              |              | B300 Pilot Duty (Same polarity)           |                |                                |
|       |                              | 4PDT         | 5A, 28 VDC (General Use) (Same polarity)  |                | 6,000                          |
|       |                              |              | 5A, 240 VAC (General Use) (Same polarity) |                |                                |
|       |                              |              | 5A, 30 VDC (Resistive) (Same polarity)    |                |                                |
|       |                              |              | 5A, 250 VAC (Resistive) (Same polarity)   |                |                                |
|       |                              |              | 0.2A, 120 VDC (Resistive) (Same polarity) |                |                                |
|       |                              |              | 1/6HP, 250 VAC (Same polarity)            |                |                                |
|       |                              |              | 1/10HP, 120 VAC (Same polarity)           |                |                                |
|       |                              |              | B300 Pilot Duty (Same polarity)           |                |                                |
|       |                              | 1,000        |   |                |                                |
|       |                              | 6,000        |   |                |                                |

### CSA 22.2 No. 14-certified Models (File No. LR31928)

| Model | Coil ratings                 | Contact form                              | Contact ratings                 | File No.                           | Certified number of operations |   |       |
|-------|------------------------------|---|---------------------------------|------------------------------------|--------------------------------|---|-------|
| MY□   | 6 to 240 VAC<br>6 to 125 VDC | DPDT                                      | 7A, 240 VAC (General Use)       | LR31928<br>(CSA C22.2)<br>(No. 14) | 6,000                          |   |       |
|       |                              |   | 7A, 24 VDC (Resistive)          |                                    |                                |   |       |
|       |                              |   | 5A, 240 VAC (General Use)       |                                    |                                |   |       |
|       |                              |   | 5A, 250 VAC (Resistive)         |                                    |                                |   |       |
|       |                              |   | 5A, 30 VDC (Resistive)          |                                    |                                |   |       |
|       |                              |   | 3A, 265 VAC (Resistive)         |                                    |                                |   |       |
|       |                              |   | 1/6HP, 250 VAC                  |                                    |                                |   |       |
|       |                              |   | 1/8HP, 265 VAC                  |                                    |                                |   |       |
|       |                              |   | 1/10HP, 120 VAC                 |                                    |                                |   |       |
|       |                              |   | B300 Pilot Duty (Same polarity) |                                    |                                |   |       |
|       |                              |   | 4PDT                            |                                    |                                | 5A, 240 VAC (General Use) (Same polarity) | 6,000 |
|       |                              |   |                                 |                                    |                                | 5A, 28 VDC (General Use) (Same polarity)  |       |
|       |                              | 5A, 250 VAC (Resistive) (Same polarity)   |                                 |                                    |                                |   |       |
|       |                              | 5A, 30 VDC (Resistive) (Same polarity)    |                                 |                                    |                                |   |       |
|       |                              | 0.2A, 120 VDC (Resistive) (Same polarity) |                                 |                                    |                                |   |       |
|       |                              | 1/6HP, 250 VAC (Same polarity)            |                                 |                                    |                                |   |       |
|       |                              | 1/10HP, 120 VAC (Same polarity)           |                                 |                                    |                                |   |       |
|       |                              | B300 Pilot Duty (Same polarity)           |                                 |                                    |                                |   |       |
|       |                              |   |                                 |                                    | 1,000                          |   |       |
|       |                              |   |                                 |                                    | 6,000                          |   |       |

### LR-certified Models (File No. 98/10014)

| Model | Coil ratings                 | Contact form | Contact ratings   | File No. | Certified number of operations                   |
|-------|------------------------------|--------------|---|----------|--|
| MY□   | 6 to 240 VAC<br>6 to 125 VDC | DPDT         | 10 A, 250 VAC (resistive)<br>2 A, 250 VAC (PF0.4)<br>10 A, 30 VDC (resistive)<br>2 A, 30 VDC (L/R = 7 ms)   | 98/10014 | MY2: 50,000 operations<br>MY4: 50,000 operations |
|       |                              | 4PDT         | 5 A, 250 VAC (resistive)<br>0.8 A, 250 VAC (PF0.4)<br>5 A, 30 VDC (resistive)<br>1.5 A, 30 VDC (L/R = 7 ms) |          |  |



# Miniature Power Relays: MY2ZN



Refer to the standards certifications and compliance section of your OMRON website for the latest information on certified models.

## Specifications

### Contact Ratings

| Item                    | Load | Resistive load                  | Inductive load<br>(cos φ = 0.4, L/R = 7 ms) |
|-------------------------|------|---------------------------------|---|
| Rated load              |      | 5 A at 220 VAC<br>5 A at 24 VDC | 2 A at 220 VAC<br>2 A at 24 VDC             |
| Rated carry current     |      | 5 A                             |   |
| Maximum contact voltage |      | 250 VAC, 125 VDC                |   |
| Maximum contact current |      | 5 A                             |   |
| Contact form            |      | DPDT (Bifurcated)               |   |
| Contact materials       |      | Au plating + Ag                 |   |

| Item                            | Type | Standard models | Model with built-in operation indicator, diode, or CR circuit |
|---------------------------------|------|-----------------|---|
| Ambient operating temperature*1 |      | -55 to 70° C    | -55 to 60° C*2  |
| Ambient operating humidity      |      | 5% to 85%       |   |

\*1. With no icing or condensation.  
\*2. This limitation is due to the diode junction temperature and elements used.

### Characteristics

| Item                        | MY2ZN series                           |   |
|-----------------------------|--|---|
| Contact resistance*1        | 50 mΩ max.                             |   |
| Operation time*2            | 20 ms max.                             |   |
| Release time*2              | 20 ms max.                             |   |
| Maximum operating frequency | Mechanical                             | 18,000 operations/h   |
|                             | Rated load                             | 1,800 operations/h  |
| Insulation resistance*3     | 100 MΩ min.                            |   |
| Dielectric strength         | Between coil and contacts              |   |
|                             | Between contacts of different polarity | 2,000 VAC at 50/60 Hz for 1 min.  |
|                             | Between contacts of the same polarity  | 1,000 VAC at 50/60 Hz for 1 min.  |
| Vibration resistance        | Destruction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)          |
|                             | Malfunfunction                         | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)          |
| Shock resistance            | Destruction                            | 1,000 m/s <sup>2</sup>  |
|                             | Malfunfunction                         | 200 m/s <sup>2</sup>  |
| Endurance                   | Mechanical                             | 50,000,000 operations min. (operating frequency: 18,000 operations/h)         |
|                             | Electrical*4                           | 200,000 operations min. (rated load, switching frequency: 1,800 operations/h) |

| Item                                     | MY2ZN           |
|--|-----------------|
| Failure rate P value (reference value)*5 | 100 μA at 1 VDC |
| Weight                                   | Approx. 35 g    |

**Note:** These are initial values.

\*1. Measurement conditions: 1 A at 5 VDC using the voltage drop method.

\*2. Measurement conditions: With rated operating power applied.

Ambient temperature condition: 23° C

\*3. Measurement conditions: For 500 VDC applied to the same location as for dielectric strength measurement.

\*4. Ambient temperature condition: 23° C


\*5. This value was measured at a switching frequency of 120 operations per minute.

# MY(S)

## Dimensions


(Unit: mm)

### MY2ZN, MY2ZN-D2




\* For the MY2Z-CR and MY2ZN-CR, this dimension is 53 mm max.

**MY2ZN**  
(AC Models)




(The coil has no polarity.)

**MY2ZN**  
(DC Models)



(Check the coil polarity when wiring and wire all connections correctly.)

**MY2ZN-D2**  
(DC Models Only)



(Check the coil polarity when wiring and wire all connections correctly.)

- Note:**
1. An AC model has coil disconnection self-diagnosis.
  2. The indicator is red for AC and green for DC.
  3. The operation indicator indicates the energization of the coil and does not represent contact operation.

# Flange-mounting Relays: MY□F



Refer to the standards certifications and compliance section of your OMRON website for the latest information on certified models.

## Specifications

### Contact Ratings

| Item                    | Contact form<br>Load            | DPDT                            |   | 4PDT, 4PDT (Bifurcated)             |   |
|-------------------------|---------------------------------|---------------------------------|---|-------------------------------------|---|
|                         |                                 | Resistive load                  | Inductive load<br>( $\cos \phi = 0.4$ , L/R = 7 ms) | Resistive load                      | Inductive load<br>( $\cos \phi = 0.4$ , L/R = 7 ms) |
| Rated load              | 5 A at 220 VAC<br>5 A at 24 VDC | 2 A at 220 VAC<br>2 A at 24 VDC | 3 A at 220 VAC<br>3 A at 24 VDC                     | 0.8 A at 220 VAC<br>1.5 A at 24 VDC |   |
| Rated carry current     | 5 A                             |                                 | 3 A   |                                     |   |
| Maximum contact voltage | 250 VAC, 125 VDC                |                                 |   |                                     |   |
| Maximum contact current | 5 A                             |                                 | 3 A   |                                     |   |
| Contact form            | DPDT                            |                                 | 4PDT, 4PDT (Bifurcated)                             |                                     |   |
| Contact materials       | Ag                              |                                 | Au plating + Ag                                     |                                     |   |

| Item                           | Type | MY□F         |
|--------------------------------|------|--------------|
| Ambient operating temperature* |      | -55 to 70° C |
| Ambient operating humidity     |      | 5% to 85%    |

\* With no icing or condensation.

### Characteristics

| Item                        | Contact form                           | DPDT  | 4PDT, 4PDT (Bifurcated)  |
|-----------------------------|--|---|--|
| Contact resistance*1        |  | 50 mΩ max.  |  |
| Operation time*2            |  | 20 ms max.  |  |
| Release time*2              |  | 20 ms max.  |  |
| Maximum operating frequency | Mechanical                             | 18,000 operations/h   |  |
|                             | Rated load                             | 1,800 operations/h  |  |
| Insulation resistance*3     |  | 100 MΩ min.   |  |
| Dielectric strength         | Between coil and contacts              |   |  |
|                             | Between contacts of different polarity | 2,000 VAC at 50/60 Hz for 1 min.  |  |
|                             | Between contacts of the same polarity  | 1,000 VAC at 50/60 Hz for 1 min.  |  |
| Vibration resistance        | Destruction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude<br>(1.0-mm double amplitude)   |  |
|                             | Malfunction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude<br>(1.0-mm double amplitude)   |  |
| Shock resistance            | Destruction                            | 1,000 m/s <sup>2</sup>  |  |
|                             | Malfunction                            | 200 m/s <sup>2</sup>  |  |
| Endurance                   | Mechanical                             | AC: 50,000,000 operations min.<br>DC: 100,000,000 operations min.<br>(switching frequency: 18,000 operations/h) |  |
|                             | Electrical*4                           | 500,000 operations min.<br>(rated load, switching frequency: 1,800 operations/h)                                | 200,000 operations min.<br>(rated load, switching frequency: 1,800 operations/h) |

| Item                                   | Contact form | DPDT          | 4PDT, 4PDT (Bifurcated) |
|--|--------------|---------------|-------------------------|
| Failure rate P value (reference value) |              | 1 mA at 5 VDC | 1 mA at 1 VDC           |
| Weight                                 |              | Approx. 35 g  |                         |

Note: These are initial values.

\*1. Measurement conditions: 1 A at 5 VDC using the voltage drop method

\*2. Measurement conditions: With rated operating power applied. Ambient temperature condition: 23° C

\*3. Measurement conditions: For 500 VDC applied to the same location as for dielectric strength measurement.

\*4. Ambient temperature condition: 23° C

\*5. This value was measured at a switching frequency of 120 operations per minute.

# MY(S)


## Dimensions

(Unit: mm)


### Flange mounting MY□F



The above figure is for the MY4F.




### Mounting Hole Dimensions




**Note:** Refer to the terminal arrangement and internal connections diagrams for the MY2(S), MY4(S) and MY4Z(S).

# Engineering Data MY□F


## Maximum Switching Capacity MY2F




## MY4F and MY4ZF




## Endurance Curve MY2F




## MY4F




## MY4ZF




## MY2F




## MY4F



## MY4ZF



## Common Specifications for MY□F Malfunctioning Shock




N = 20

Measurement: Shock was applied 3 times each in 6 directions along 3 axes with the Relay energized and not energized to check the shock values that cause the Relay to malfunction.

Criteria: Non-energized: 200 m/s<sup>2</sup>,

Energized: 200 m/s<sup>2</sup>

### Shock direction



# MY(S)

## Detailed Information on Models Certified for Safety Standards, MY2ZN and MY□F

- The standard models are certified for UL and CSA standards.
- The rated values for safety standard certification are not the same as individually defined performance values. Always check the specifications before use.

### TÜV-certified Models (File No. R50030059)

| Model | Coil ratings                 | Contact form | Contact ratings  | Certified number of operations |
|-------|------------------------------|--------------|--|--------------------------------|
| MY□   | 6 to 125 VDC<br>6 to 240 VDC | DPDT         | 5 A, 250 VAC (cos φ = 1.0)                                 | 100,000 operations             |
|       |                              | 4PDT         | 3 A, 120 VAC (cos φ = 1.0)<br>0.8 A, 120 VAC (cos φ = 0.4) |                                |

### UL-certified Models (File No. E41515)

| Model                                     | Coil ratings                 | Contact form | Contact ratings                           | Certified number of operations |
|---|------------------------------|--------------|---|--------------------------------|
| MY□                                       | 6 to 240 VAC<br>6 to 125 VDC | DPDT         | 7A, 240 VAC (General Use)                 | 6,000                          |
|   |                              |              | 7A, 24 VDC (Resistive)                    |                                |
|   |                              |              | 5A, 240 VAC (General Use)                 |                                |
|   |                              |              | 5A, 250 VAC (Resistive)                   |                                |
|   |                              |              | 5A, 30 VDC (Resistive)                    |                                |
|   |                              |              | 3A, 265 VAC (Resistive)                   |                                |
|   |                              |              | 1/6HP, 250 VAC                            |                                |
|   |                              | 4PDT         | 1/8HP, 265 VAC                            | 1,000                          |
|   |                              |              | 1/10HP, 120 VAC                           |                                |
|   |                              |              | B300 Pilot Duty                           |                                |
|   |                              | 4PDT         | 5A, 28 VDC (General Use) (Same polarity)  | 6,000                          |
|   |                              |              | 5A, 240 VAC (General Use) (Same polarity) |                                |
|   |                              |              | 5A, 30 VDC (Resistive) (Same polarity)    |                                |
|   |                              |              | 5A, 250 VAC (Resistive) (Same polarity)   |                                |
| 0.2A, 120 VDC (Resistive) (Same polarity) |                              |              |   |                                |
| 1/6HP, 250 VAC (Same polarity)            | 1,000                        |              |   |                                |
| 1/10HP, 120 VAC (Same polarity)           |                              |              |   |                                |
| B300 Pilot Duty (Same polarity)           | 6,000                        |              |   |                                |

### CSA-certified Models (File No. LR31928)

| Model           | Coil ratings                 | Contact form | Contact ratings                           | Certified number of operations |
|-----------------|------------------------------|--------------|---|--------------------------------|
| MY□             | 6 to 240 VAC<br>6 to 125 VDC | DPDT         | 7A, 240 VAC (Resistive)                   | 6,000                          |
|                 |                              |              | 7A, 24 VDC (Resistive)                    |                                |
|                 |                              |              | 5A, 240 VAC (General Use)                 |                                |
|                 |                              |              | 5A, 250 VAC (Resistive)                   |                                |
|                 |                              |              | 5A, 30 VDC (Resistive)                    |                                |
|                 |                              |              | 1/6HP, 250 VAC                            |                                |
|                 |                              | 4PDT         | 1/10HP, 120 VAC                           | 1,000                          |
|                 |                              |              | 7A, 240 VAC (General Use) (Same polarity) |                                |
|                 |                              |              | 7A, 24 VDC (Resistive) (Same polarity)    |                                |
|                 |                              |              | 5A, 240 VAC (General Use) (Same polarity) |                                |
|                 |                              |              | 5A, 30 VDC (Resistive)                    |                                |
|                 |                              |              | 5A, 250 VAC (Resistive) (Same polarity)   |                                |
|                 |                              |              | 0.2A, 120 VDC (Resistive)                 |                                |
|                 |                              |              | 1/6HP, 250 VAC                            |                                |
| 1/10HP, 120 VAC | 1,000                        |              |   |                                |

- When ordering models that are certified for Lloyd's Register (LR) Standards, be sure to specify "LR-certified Model" with your order.

### LR-certified Models (File No. 90/10270)

| Model | Coil ratings                 | Contact form | Contact ratings  |
|-------|------------------------------|--------------|--|
| MY□   | 6 to 240 VAC<br>6 to 125 VDC | DPDT         | 2 A, 30 VDC inductive load<br>2 A, 200 VAC inductive load                                      |
|       |                              | 4PDT         | 1.5 A, 30 VDC inductive load<br>0.8 A, 200 VAC inductive load<br>1.5 A, 115 VAC inductive load |

# Miniature Power Relays: MY4Z-CBG

## Specifications

### Contact Ratings

| Item                    | Load | Resistive load                  | Inductive load<br>( $\cos \varphi = 0.4, L/R = 7 \text{ ms}$ ) |
|-------------------------|------|---------------------------------|--|
| Rated load              |      | 1 A at 220 VAC<br>1 A at 24 VDC | 0.3 A at 220 VAC<br>0.5 A at 24 VDC                            |
| Rated carry current     |      | 1 A                             |  |
| Maximum contact voltage |      | 250 VAC, 125 VDC                |  |
| Maximum contact current |      | 1 A                             |  |
| Contact form            |      | 4PDT (Crossbar bifurcated)      |  |
| Contact materials       |      | Au cladding + AgPd              |  |

### Characteristics

|  |  |  |
|--|--|--|
| Contact resistance*1                     |  | 100 mΩ max.  |
| Operation time*2                         |  | 20 ms max.   |
| Release time*2                           |  | 20 ms max.   |
| Maximum operating frequency              | Mechanical                             | 18,000 operations/h  |
|  | Electrical                             | 1,800 operations/h   |
| Insulation resistance*3                  |  | 100 MΩ   |
| Dielectric strength                      | Between coil and contacts              | 2,000 VAC at 50/60 Hz for 1 min.   |
|  | Between contacts of different polarity |  |
|  | Between contacts of the same polarity  | 700 VAC at 50/60 Hz for 1 min.   |
| Vibration resistance                     | Destruction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)           |
|  | Malfunction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)           |
| Shock resistance                         | Destruction                            | 1,000 m/s <sup>2</sup>   |
|  | Malfunction                            | 200 m/s <sup>2</sup>   |
| Endurance                                | Mechanical                             | 5,000,000 operations min. (operating frequency: 18,000 operations/hr)          |
|  | Electrical*4                           | 50,000 operations min. (switching frequency: 1,800 operations/h) at rated load |
| Failure rate P value (reference value)*5 |  | 100 μA at 1 VDC  |
| Ambient operating temperature            |  | -25 to 70°C (with no icing or condensation)                                    |
| Ambient operating humidity               |  | 5% to 85%  |
| Weight                                   |  | Approx. 35 g   |


Note: The above values are initial values.

- \*1. Measurement conditions: 1 A at 5 VDC using the voltage drop method
- \*2. Measurement conditions: With rated operating power applied, not including contact bounce.  
Ambient temperature condition: 23° C
- \*3. Measurement conditions: For 500 VDC applied to the same location as for dielectric strength measurement.
- \*4. Ambient temperature condition: 23° C
- \*5. This value was measured at a switching frequency of 120 operations per minute.

## Engineering Data


### Maximum Switching Capacity

#### MY4Z-CBG



### Contact Reliability Test (Modified Allen Bradley Circuit)

Contact load: 5 VDC, 1 mA resistive load  
Malfunction criteria level: Contact resistance of 100 Ω




# MY(S)


## Dimensions

(Unit: mm)

### MY4Z-CBG



### Terminal Arrangement/Internal Connections (Bottom View) Standard Models



## Safety Precautions

Refer to the *Common Relay Precautions*.

### Applicable Sockets

Use only combinations of OMRON Relays and Sockets.



# Plastic Sealed Relays: MYQ4

## Specifications

### Contact Ratings

| Item  | Type | Resistive load  | Inductive load<br>( $\cos \phi = 0.4, L/R = 7 \text{ ms}$ ) |
|---|------|---|---|
| Rated load                                      |      | 1 A at 220 VAC, 1 A at 24 VDC   | 0.5 A at 220 VAC, 0.5 A at 24 VDC                           |
| Rated carry current                             |      | 1 A   |   |
| Maximum contact voltage                         |      | 250 VAC, 125 VDC  |   |
| Maximum contact current                         |      | 1 A   |   |
| Maximum switching capacity<br>(reference value) |      | 220 VAC, 24 W   | 110 VAC, 12 W   |
| Failure rate P value<br>(reference value)       |      | Single contacts: 1 mA at 1 VDC, Bifurcated contacts: 100 $\mu\text{A}$ at 1 VDC |   |
| Contact form                                    |      | 4PDT, 4PDT (Bifurcated)   |   |
| Contact materials                               |      | Au plating + Ag   |   |

\* This value was measured at a switching frequency of 120 operations per minute.

|                               |               |
|-------------------------------|---------------|
| Ambient operating temperature | -55 to 60° C* |
| Ambient operating humidity    | 5% to 85%     |

\* With no icing or condensation.

### Characteristics

|                             |  |  |
|-----------------------------|--|--|
| Contact resistance*1        |  | 50 m $\Omega$ max.   |
| Operation time*2            |  | 20 ms max.   |
| Release time*2              |  | 20 ms max.   |
| Maximum operating frequency | Mechanical                             | 18,000 operations/h  |
|                             | Rated load                             | 1,800 operations/h   |
| Dielectric strength         | Between coil and contacts              | 1,500 VAC at 50/60 Hz for 1 min.   |
|                             | Between contacts of different polarity | 1,500 VAC at 50/60 Hz for 1 min.   |
|                             | Between contacts of the same polarity  | 1,000 VAC at 50/60 Hz for 1 min.   |
| Insulation resistance*3     |  | 100 M $\Omega$ min.  |
| Vibration resistance        | Destruction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)   |
|                             | Malfunction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)   |
| Shock resistance            | Destruction                            | 1,000 m/s <sup>2</sup>   |
|                             | Malfunction                            | 200 m/s <sup>2</sup>   |
| Endurance                   | Mechanical                             | AC: 50,000,000 operations (5,000,000*4) min., DC: 100,000,000 operations (5,000,000*4) min. (switching frequency: 18,000 operations/h) |
|                             | Electrical*5                           | 200,000 operations min. (100,000 operations*4) (rated load, switching frequency: 1,800 operations/h)                                   |
| Weight                      |  | Approx. 35 g   |

**Note:** The values at the left are initial values.

\*1. Measurement conditions: 1 A at 5 VDC using the voltage drop method

\*2. Measurement conditions: With rated operating power applied, not including contact bounce. Ambient temperature condition: 23° C


\*3. Measurement conditions: For 500 VDC applied to the same location as for dielectric strength measurement.

\*4. This value is for bifurcated contacts.


\*5. Ambient temperature condition: 23° C

## Engineering Data

### Maximum Switching Capacity MYQ4(Z)




### Endurance Curve MYQ4




**Note:** The durability of bifurcated contacts is one-half that of single contacts.

### H<sub>2</sub>S Gas Data MYQ4



### Malfunctioning Shock MYQ4





N = 20  
Measurement: Shock was applied 3 times each in 6 directions along 3 axes with the Relay energized and not energized to check the shock values that cause the Relay to malfunction.  
Criteria: Non-energized: 200 m/s<sup>2</sup>  
Energized: 200 m/s<sup>2</sup>

# MY(S)

## Dimensions

(Unit: mm)

### Relays with Plug-in Terminals or Soldered Terminals MYQ4(Z)(N)



- Note:**
1. An AC model has coil disconnection self-diagnosis.
  2. For the DC models, check the coil polarity when wiring and wire all connections correctly.

## Safety Precautions

- For models with built-in operation indicators, check the coil polarity when wiring and wire all connections correctly (DC operation).
- Use only combinations of OMRON Relays and Sockets.

### Relay Replacement

To replace the Relay, turn OFF the power supply to the load and Relay coil sides to prevent unintended operation and possible electrical shock.

# Latching Relays: MY2K

## Specifications

### Coil Rating

| Item | Rated voltage (V) | Set coil           |       |                     | Reset coil         |       |                     | Set voltage (V) | Reset voltage (V) | Maximum voltage (V)        | Power consumption (VA, W)     |                               |
|------|-------------------|--------------------|-------|---------------------|--------------------|-------|---------------------|-----------------|-------------------|----------------------------|-------------------------------|-------------------------------|
|      |                   | Rated current (mA) |       | Coil resistance (Ω) | Rated current (mA) |       | Coil resistance (Ω) |                 |                   |                            | Set coil                      | Reset coil                    |
|      |                   | 50 Hz              | 60 Hz |                     | 50 Hz              | 60 Hz |                     |                 |                   |                            |                               |                               |
| AC   | 12                | 57                 | 56    | 72                  | 39                 | 38.2  | 130                 | 80% max.        | 80% max.          | 110% max. of rated voltage | Approx. 0.6 to 0.9 (at 60 Hz) | Approx. 0.2 to 0.5 (at 60 Hz) |
|      | 24                | 27.4               | 26.4  | 320                 | 18.6               | 18.1  | 550                 |                 |                   |                            |                               |                               |
|      | 100               | 7.1                | 6.9   | 5,400               | 3.5                | 3.4   | 3,000               |                 |                   |                            |                               |                               |
| DC   | 12                | 110                |       | 110                 | 50                 |       | 235                 | 80% max.        | 80% max.          | 110% max. of rated voltage | Approx. 1.3                   | Approx. 0.6                   |
|      | 24                | 52                 |       | 470                 | 25                 |       | 940                 |                 |                   |                            |                               |                               |
|      | 48                | 27                 |       | 1,800               | 16                 |       | 3,000               |                 |                   |                            |                               |                               |

- Note:**
1. The rated current for AC is the value measured with a DC ammeter in half-wave rectification.
  2. The rated current and coil resistance are measured at a coil temperature of 23°C with tolerances of +15%/–20% for the AC rated current and ±15% for the DC coil resistance.
  3. The AC coil resistance is a reference value only.
  4. Operating characteristics were measured at a coil temperature of 23°C.
  5. The maximum voltage capacity was measured at an ambient temperature of 23°C.

### Contact Ratings

| Item                          | Load | Resistive load                  | Inductive load (cos φ = 0.4, L/R = 7 ms) |
|-------------------------------|------|---------------------------------|--|
| Rated load                    |      | 3 A at 220 VAC<br>3 A at 24 VDC | 0.8 A at 220 VAC<br>1.5 A at 24 VDC      |
| Rated carry current           |      | 3 A                             |  |
| Maximum contact voltage       |      | 250 VAC, 125 VDC                |  |
| Maximum contact current       |      | 3 A                             |  |
| Contact form                  |      | DPDT                            |  |
| Contact materials             |      | Au plating + Ag                 |  |
| Ambient operating temperature |      | –55 to 60° C*                   |  |
| Ambient operating humidity    |      | 5% to 85%                       |  |

\* With no icing or condensation.

### Characteristics

|  |  |  |
|--|--|--|
| Contact resistance*1                     |  | 50 mΩ max.   |
| Set                                      | Time*2                                 | AC: 30 ms max., DC: 15 ms max.   |
|  | Minimum pulse width                    | AC: 60 ms, DC: 30 ms   |
| Reset                                    | Time*2                                 | AC: 30 ms max., DC: 15 ms max.   |
|  | Minimum pulse width                    | AC: 60 ms, DC: 30 ms   |
| Maximum operating frequency              | Mechanical                             | 18,000 operations/h  |
|  | Rated load                             | 1,800 operations/h   |
| Insulation resistance*3                  |  | 100 MΩ   |
| Dielectric strength                      | Between coil and contacts              | 1,500 VAC at 50/60 Hz for 1 min.                                       |
|  | Between contacts of different polarity |  |
|  | Between contacts of the same polarity  | 1,000 VAC at 50/60 Hz for 1 min.                                       |
| Between set/reset coils                  |  |  |
| Vibration resistance                     | Destruction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)   |
|  | Malfunction                            | 10 to 55 to 10 Hz, 0.5-mm single amplitude (1.0-mm double amplitude)   |
| Shock resistance                         | Destruction                            | 1,000 m/s <sup>2</sup>   |
|  | Malfunction                            | 200 m/s <sup>2</sup>   |
| Endurance                                | Mechanical                             | 100,000,000 operations min. (switching frequency: 18,000 operations/h) |
|  | Electrical*4                           | 200,000 operations min. (at 1,800 operations/hr, rated load)           |
| Failure rate P value (reference value)*5 |  | 1 mA at 1 VDC  |
| Weight                                   |  | Approx. 30 g   |


**Note:** The above values are initial values.

- \*1. Measurement conditions: 1 A at 5 VDC using the voltage drop method
- \*2. Measurement conditions: With rated operating power applied, not including contact bounce.
- \*3. Measurement conditions: For 500 VDC applied to the same location as for dielectric strength measurement.
- \*4. Ambient temperature condition: 23° C
- \*5. This value was measured at a switching frequency of 120 operations per minute.



# MY(S) Engineering Data

## MY2K



### Maximum Switching Capacity



### Endurance Curve




### MY2K 100 VAC Malfunctioning Shock




**N = 20**  
Measurement: Shock was applied 2 times each in 6 directions along 3 axes with the Relay energized and not energized to check the shock values that cause the Relay to malfunction.  
Criteria: Non-energized: 200 m/s<sup>2</sup>  
Energized: 200 m/s<sup>2</sup>

### MY2K 24 VDC Magnetic Interference (External Magnetic Field)




### Latching Deterioration Over Time




## Dimensions

(Unit: mm)

### Relays with Plug-in Terminals or Soldered Terminals MY2K




### Terminal Arrangement/Internal Connections (Bottom View)



**Note:** R is a resistor for ampere-turn correction. This resistor is built-in to 50-VAC and higher models. (The coil has no polarity.)

## Safety Precautions

- For applications that use a 200 VAC power supply, connect external resistors  $R_s$  and  $R_r$  to a 100 VAC Relay.
- Do not apply a voltage to the set and reset coils at the same time. If you apply the rated voltage to both coils simultaneously, the Relay will be set.
- The minimum pulse width in the performance column is the value for the following measurement conditions: an ambient temperature of 23° C with the rated operating voltage applied to the coil. The performance values given here may not be satisfied due to use over time and a reduction in latching performance due to changes in the ambient temperature or in the conditions of the application circuit.  
For actual use, apply the rated operating voltage with a pulse width based on the actual load and reset the Relay at least once per year to prevent degradation over time.
- If the Relay is used in an environment with strong magnetic fields, the surrounding magnetic field can demagnetize the magnetic body and cause unintended operation. Therefore, do not use these Relays in environments with strong magnetic fields.



### Relay Replacement

To replace the Relay, turn OFF the power supply to the load and Relay coil sides to prevent unintended operation and possible electrical shock.

### Applicable Sockets

Use only combinations of OMRON Relays and Sockets.

# Hermetically Sealed Relays: MY4(Z)H

## Specifications

### Contact Ratings

| Item                          | Load                            | MY4H                                |   | MY4ZH                               |   |
|-------------------------------|---------------------------------|-------------------------------------|---|-------------------------------------|---|
|                               |                                 | Resistive load                      | Inductive load<br>cos φ = 0.4<br>L/R = 7 ms | Resistive load                      | Inductive load<br>cos φ = 0.4<br>L/R = 7 ms |
| Rated load                    | 3 A at 110 VAC<br>3 A at 24 VDC | 0.8 A at 110 VAC<br>1.5 A at 24 VDC | 3 A at 110 VAC<br>3 A at 24 VDC             | 0.8 A at 110 VAC<br>1.5 A at 24 VDC |   |
| Rated carry current           | 3 A                             |                                     |   |                                     |   |
| Maximum contact voltage       | 125 VAC<br>125 VDC              |                                     |   |                                     |   |
| Maximum contact current       | 3 A                             |                                     |   |                                     |   |
| Contact form                  | 4DPDT                           |                                     | 4DPDT (Bifurcated)                          |                                     |   |
| Contact materials             | Au plating + Ag                 |                                     |   |                                     |   |
| Ambient operating temperature | -25 to 60° C*                   |                                     |   |                                     |   |
| Ambient operating humidity    | 5% to 85%                       |                                     |   |                                     |   |

\* With no icing or condensation.

### Characteristics


|  |   |   |
|--|---|---|
| Contact resistance*1                     | 50 mΩ max.  |   |
| Operation time*2                         | 20 ms max.  |   |
| Release time*2                           | 20 ms max.  |   |
| Maximum operating frequency              | Mechanical  | 18,000 operations/h   |
|  | Rated load  | 1,800 operations/h  |
| Insulation resistance*4                  | 100 MΩ min.   |   |
| Dielectric strength                      | Between coil and contacts   | 1,000 VAC at 50/60 Hz for 1 min.<br>(700 VAC between contacts of the same polarity.)              |
|  | Between contacts of different polarity                                      |   |
| Vibration resistance                     | Destruction   | 10 to 55 to 10 Hz, 0.5-mm single amplitude<br>(1.0-mm double amplitude)                           |
|  | Malfunction   | 10 to 55 to 10 Hz, 0.5-mm single amplitude<br>(1.0-mm double amplitude)                           |
| Shock resistance                         | Destruction   | 1,000 m/s <sup>2</sup>  |
|  | Malfunction   | 200 m/s <sup>2</sup>  |
| Endurance                                | Mechanical  | 50,000,000 operations (5,000,000 operations*4) min.<br>(operating frequency: 18,000 operations/h) |
|  | Electrical*5  | 100,000 operations (50,000 operations*4) min. rated load, switching frequency: 1,800 operations/h |
| Failure rate P value (reference value)*6 | Single contacts: 100 μA at 1 VDC<br>Bifurcated contacts: 100 μA at 100 mVDC |   |
| Weight                                   | Approx. 50 g  |   |

Note: The above values are initial values.


- \*1. Measurement conditions: 1 A at 5 VDC using the voltage drop method
- \*2. Measurement conditions: With rated operating power applied, not including contact bounce.  
Ambient temperature condition: 23° C
- \*3. Measurement conditions: For 500 VDC applied to the same location as for dielectric strength measurement.
- \*4. This value is for bifurcated contacts.
- \*5. Ambient temperature condition: 23° C
- \*6. This value was measured at a switching frequency of 120 operations per minute.

## Engineering Data

### Maximum Switching Capacity MY4(Z)H



### Endurance Curve MY4H




Note: The durability of bifurcated contacts is one-half that of single contacts.

# MY(S)


## Dimensions

(Unit: mm)

### Relays with Plug-in Terminals or Soldered Terminals MY4(Z)H



### Terminal Arrangement/ Internal Connections (Bottom View)



(The coil has no polarity.)

## Safety Precautions

### Applicable Sockets

Use only combinations of OMRON Relays and Sockets.

### Application Environment for Hermetically Sealed Relays

Humid environments can cause insulation problems, which may result in short-circuiting or unintended operation.

### Solution

Do not use these Relays in any environment where the Relay will come into contact with water vapor, condensation, or water droplets. This can reduce the surface tension of the insulating beads and cause short-circuiting or unintended operation due to poor insulation.

### Relay Replacement


To replace the Relay, turn OFF the power supply to the load and Relay coil sides to prevent unintended operation and possible electrical shock.

# Sockets for MY

## DIN-rail-mounted (DIN-rail) Socket Conforms to VDE 0106, Part 100









- Snap into position along continuous sections of any mounting DIN-rail.
- Facilitates sheet metal design by standardized mounting dimensions.
- Design with sufficient dielectric separation between terminals eliminates the need of any insulating sheet.



## Specifications

| Mounting                | Terminal type          | No. of poles   | Appearance | Model                 | Carry current    | Dielectric withstand voltage | Insulation resistance (see note 2) |
|-------------------------|------------------------|----------------|------------|-----------------------|------------------|------------------------------|------------------------------------|
| DIN-rail-mounted Socket | Push-In Plus terminals | 2              |            | PYF-08-PU             | 10 A             | 2,000 VAC, 1 min             | 1,000 MΩ min                       |
|                         |                        | 4              |            | PYF-14-PU             | 6 A              |                              |                                    |
|                         | Screw terminals        | 2              |            | PYFZ-08-E/<br>PYFZ-08 | 10 A             | 2,250 VAC, 1 min             | 1,000 MΩ min                       |
|                         |                        |                |            | PYF08A-N (see note 3) | 7 A (see note 4) | 2,000 VAC, 1 min             |                                    |
|                         |                        | 4              |            | PYFZ-14-E/<br>PYFZ-14 | 6 A              | 2,250 VAC, 1 min             |                                    |
|                         |                        |                |            | PYF14A-N (see note 3) | 5 A (see note 4) | 2,000 VAC, 1 min             |                                    |
|                         | Rise-Up terminals      | 2 and 4 Common |            | PYF14-ESS-B           | 12 A             | > 3 KV                       | > 5 MΩ                             |
|                         |                        |                |            | PYF14-ESN-B           |                  |                              |                                    |

# MY(S)

| Mounting        | Terminal type             | No. of poles | Appearance  | Model                | Carry current | Dielectric withstand voltage | Insulation resistance (see note 2) |
|-----------------|---------------------------|--------------|---|----------------------|---------------|------------------------------|------------------------------------|
| Back-connecting | Solder terminals          | 2            |  | PY08/<br>PY08-Y1     | 7 A           | 1,500 VAC, 1 min             | 1000 MΩ min.                       |
|                 |                           | 4            |  | PY14/<br>PY14-Y1     | 3 A           |                              | 100 MΩ min.                        |
|                 | Wrapping terminals        | 2            |  | PY08QN/<br>PY08QN-Y1 | 7 A           |                              |                                    |
|                 |                           | 4            |  | PY14QN/<br>PY14QN-Y1 | 3 A           |                              |                                    |
|                 | Relays with PCB terminals | 2            |  | PY08-02              | 7 A           |                              |                                    |
|                 |                           | 4            |  | PY14-02              | 3 A           |                              |                                    |

- Note:**
1. The values given above are initial values.
  2. The values for insulation resistance were measured at 500 VDC at the same place as the dielectric strength.
  3. The maximum operating ambient temperature for the PYF08A-N and PYF14A-N is 55°C.
  4. When using the PYF08A-N or PYF14A-N at an operating ambient temperature exceeding 40°C, reduce the current to 60%.
  5. The MY2(S) can be used at 70°C with a carry current of 7 A.



## Options (Order Separately)

### Connection Socket and Mounting Bracket Selection Table

(The possible combinations of models with plug-in terminals and sockets)

| Connecting method<br>Mounting method |   | Front-mounting Sockets (PYF□)          |  |  |                                | Back-mounting Sockets (PY□)  |                        |                              |                        |                              |                        |   |
|--------------------------------------|---|--|--|--|--------------------------------|------------------------------|------------------------|------------------------------|------------------------|------------------------------|------------------------|---|
|                                      |   | Track or screw mounting                |  |  |                                | Solder terminals             |                        |                              |                        |                              |                        |   |
|                                      |   | Screw terminals                        | Screw terminals<br>(finger protection structure) | Rise-Up terminals                                | Push-In Plus Terminal Block *2 | Wrapping terminals           |                        |                              |                        | Relays with PCB Terminals *3 |                        |   |
| Terminal length: 25 mm               |   |  |  |  |                                | Terminal length: 20 mm       |                        |                              |                        |                              |                        |   |
| No. of poles                         | Model   | (Order separately: Hold-down Clips) *1 |  | Without Release Lever                            | With Release Lever             | Without Mounting Brackets *1 | With Mounting Brackets | Without Mounting Brackets *1 | With Mounting Brackets | Without Mounting Brackets *1 | With Mounting Brackets | (Order separately : Hold-down Clips) *1 |
| 8                                    | MY2(S), MY2ZN (except for MY2K□, MY2Z□-CR)    | PYFZ-08 (PYC-A1)                       | PYFZ-08-E (PYC-A1)<br>PYF08A-N (PYC-A1)          | PYF14-ESN-B (PYC-35-B)<br>PYF14-ESS-B (PYC-35-B) | PYF-08-PU                      | PY08 (PYC-P)                 | PY08-Y1                | PY08QN (PYC-P)               | PY08QN-Y1              | PY08QN2 (PYC-P)              | PY08QN2-Y1             | PY08-02 (PYC-P)                         |
|                                      | MY2I(S) *4                                    | PYFZ-08 (PYC-E1)                       | PYFZ-08-E (PYC-E1)<br>PYF08A-N (PYC-E1)          |  |                                | PY08 (PYC-1)                 | PY08-Y3                | PY08QN (PYC-1)               | /                      | PY08QN2 (PYC-1)              | /                      | PY08-02 (PYC-1)                         |
|                                      | MY2Z-□-CR *5                                  | PYFZ-08 (Y92H-3)                       | PYFZ-08-E (Y92H-3)<br>PYF08A-N (Y92H-3)          |  |                                | PY14 (PYC-P)                 | PY14-Y1                | PY14QN (PYC-P)               | PY14QN-Y1              | PY14QN2 (PYC-P)              | PY14QN2-Y1             | PY14-02 (PYC-P)                         |
| 14                                   | MY4(S), MY4I(S), MY4-CBG, MY4Q, MY4(Z)H, MY2K | PYFZ-14 (PYC-A1)                       | PYFZ-14-E (PYC-A1)<br>PYF14A-N (PYC-A1)          |  | PYF-14-PU                      | PY14 (PYC-P)                 | PY14-Y1                | PY14QN (PYC-P)               | PY14QN-Y1              | PY14QN2 (PYC-P)              | PY14QN2-Y1             | PY14-02 (PYC-P)                         |

**Note:** Refer to Common Socket and DIN Track Products for the external dimensions of the Socket Relays and details on Hold-down Clips.

\*1. The information in parentheses is the model number of the applicable Mounting Bracket. Mounting Brackets are sold in sets of two. However, the PYC-P is just one Mounting Bracket.

\*2. A Push-In Plus Terminal Block Socket functions as a release lever to hold or remove a Relay. Refer to PYF-□□-PU/P2RF-□□-PU for details.

\*3. If an MYI□(S) Relay with a Latching Lever is used in combination with a PY□-02 Socket for Relays with PCB Terminal Socket and PYC-P Mounting Brackets, the lever will not operate.

\*4. We recommends using the PYC-E1 Mounting Bracket for a MY2I(S) Relay with Latching Lever. (If the PYC-A1 is used with the MY2I(S), the latching lever will be blocked by the Mounting Bracket and the lever will not operate.)

\*5. The Mounting Brackets are applicable for Relays with a height of 36 mm or less. If the Relay height is greater than 53 mm, use Y92H-3 for the Front-mounting Socket and PYC-1 for the Back-mounting Socket. (The Y92H-3 is a set of two Brackets and the PYC-1 is just one Bracket.)

### Terminal Covers for PYFZ-08/PYFZ-14 Sockets

| Applicable model | Model                |
|------------------|----------------------|
| PYFZ-08          | PYCZ-C08 (2 pcs/set) |
| PYFZ-14          | PYCZ-C14 (1 pcs/set) |

**Note:** Use these covers in a combination with PYFZ-08 and PYFZ-14.

### Mounting Plates for Sockets

| Socket model                     | For 1 Socket | For 18 Sockets | For 36 Sockets |
|----------------------------------|--------------|----------------|----------------|
| PY08, PY08QN(2), PY14, PY14QN(2) | PYP-1        | PYP-18         | PYP-36         |

**Note:** PYP-18 and PYP-36 can be cut into any desired length in accordance with the number of Sockets.

### DIN-rail and Accessories

|   |                     |
|---|---------------------|
| Supporting DIN-rail (length = 500 mm)       | PFP-50N             |
| Supporting DIN-rail (length = 1,000 mm) PFP | PFP-100N, PFP-100N2 |
| End Plate                                   | PFP-M               |
| Spacer                                      | PFP-S               |


## Safety Standards for Sockets

### Front-mounted Sockets (PYF□)

| Model                                    | Standards         | File No.              |
|--|-------------------|-----------------------|
| PYF-08-PU<br>PYF-14-PU                   | TÜV (EN 61984)    | ---                   |
|  | UL508             | E87929                |
|  | CSA C22.2 No.14   | ---                   |
| PYF14A-E, PYF14A-N                       | VDE0627 (EN61984) | Nr.B387 (License No.) |
| PYFZ-08-E, PYFZ-08<br>PYFZ-14-E, PYFZ-14 | TÜV(EN 61984)     | R50405329             |
|  | UL508             | E87929                |
|  | CSA22.2           | LR31928               |
| PYF08A-N<br>PYF14A-N                     | TÜV(EN 61984)     | J50224549             |
|  | UL508             | E87929                |
|  | CSA22.2           | LR31928               |
| PYF14-ESN-B<br>PYF14-ESS-B               | UL508             | E244189               |
|  | CSA22.2           | LR225761              |

### Back-connecting Sockets (PY□)

| Model                  | Standards | File No. |
|------------------------|-----------|----------|
| PY08(-02)<br>PY14(-02) | UL508     | E87929   |
|                        | CSA C22.2 | LR31928  |






## Mounting Heights with Sockets (Unit: mm)


### Front-mounting Sockets

#### Screw terminal

(PYFZ-□ (-E), PYF□A-N, PYF14-ES□-B)



#### Push-In Plus Terminal Block Sockets (PYF-□-PU)




Note: 1. The heights given in parentheses are the measurements for 53-mm-high Relays.


### Back-mounting Sockets

#### Solder terminals/Wrapping terminals

(PY□)



















#### Relays with PCB Terminals (PY□-02)































Dimensions



















(Unit: mm)

Note: All units are in millimeters unless otherwise indicated.

| Socket  | Dimensions   | Terminal arrangement/<br>Internal connections (top view)  | Mounting holes  |
|---|--|---|---|
| <p>PYF-08-PU</p>   |  <p>71.5</p> <p>67.5</p> <p>30.8</p> <p>28.1</p> <p>25.6</p> <p>(4.2)</p> <p>Coil short bar insertion holes</p> <p>90</p> <p>35.3</p> <p>27.35</p> <p>3.9</p> <p>25.6</p> <p>34.3</p> <p>43</p> <p>52.1</p> <p>31</p> <p>(4.2)</p> <p>Contact short bar insertion holes</p> |  <p><b>Note1:</b> The numbers in parentheses are traditionally used terminal numbers.</p> <p><b>Note2:</b> Insert the short bar into only the A1 or A2 side.</p> <p><b>Note3:</b> Only the No. 11 and No. 41 terminals function as bridging contact terminals. The two insertion holes between the terminals are false terminals to allow for installation without having to fold out the short bar pins.</p> |  <p>Two M3 screw holes or two 3.5-dia. holes</p> <p>108</p> <p><b>Note 1:</b> Pull out the hooks to mount the Socket with screws.</p> <p><b>Note 2:</b> DIN-rail mounting is also possible. Refer to page 34 for supporting DIN-rails.</p> |
| <p>PYFZ-08-E</p>  |  <p>Two, 4.2 × 5 <math>6^{+0.2}_{-0.1}</math> mounting holes</p> <p>Eight, M3 × 8</p> <p>72 max.</p> <p>35.4</p> <p>4</p> <p>23 max.</p> <p>31 max.</p> <p>6</p>   |   |  <p>Two, M3, M4, or 4.5-dia. holes</p> <p>59±0.3</p> <p>15±0.2</p> <p>(TOP VIEW)</p> <p><b>Note:</b> DIN-rail mounting is also possible. Refer to page 34 for supporting DIN-rails.</p>   |
| <p>PYF08A-N</p>  |  <p><math>6^{+0.2}_{-0.1}</math></p> <p>Eight, M3×8</p> <p>67 max.</p> <p>73</p> <p>22 max.</p> <p>30 max.</p>  |  <p><b>Note:</b> Figures in parentheses indicate DIN standard numbers.</p>  |  <p>3.0 dia.</p> <p>18.7</p> <p>3.5 dia. or M3</p> <p><b>Note:</b> DIN-rail mounting is also possible. Refer to page 34 for supporting DIN-rails.</p>  |
| <p>PYFZ-08</p>   |  <p>Two, 4.2 × 5 <math>6^{+0.2}_{-0.1}</math> mounting holes</p> <p>8-M3 × 8</p> <p>72 max.</p> <p>35.4</p> <p>4</p> <p>23 max.</p> <p>30 max.</p> <p>6</p>   |   |  <p>Two, M3, M4, or 4.5-dia. holes</p> <p>59±0.3</p> <p>15±0.2</p> <p>(TOP VIEW)</p> <p><b>Note:</b> DIN-rail mounting is also possible. Refer to page 34 for supporting DIN-rails.</p>  |

| Socket  | Dimensions   | Terminal arrangement/<br>Internal connections (top view)   | Mounting holes  |
|---|--|--|---|
| <p>PYF-14-PU</p>   |  <p>Coil short bar insertion holes</p> <p>Contact short bar insertion holes</p> |  <p><b>Note:</b> The numbers in parentheses are traditionally used terminal numbers.</p> |  <p>Two M3 screw holes or two 3.5-dia. holes</p> <p>108</p> <p><b>Note 1:</b> Pull out the hooks to mount the Socket with screws.</p> <p><b>Note 2:</b> DIN-rail mounting is also possible. Refer to page 34 for supporting DIN-rails.</p> |
| <p>PYFZ-14-E</p>   |  <p>Two, 4.2 x 5 mounting holes</p> <p>Fourteen, M3 x 8 sems screws</p>        |   |  <p>Two, M3, M4, or 4.5-dia. holes</p> <p>59±0.3</p> <p>22±0.2</p> <p>(TOP VIEW)</p> <p><b>Note:</b> DIN-rail mounting is also possible. Refer to page 34 for supporting DIN-rails.</p>   |
| <p>PYF14A-N</p>  |  <p>Fourteen, M3x8</p>  |  <p><b>Note:</b> Figures in parentheses indicate DIN standard numbers.</p>             |  <p>Two, 4.5 dia. or M4</p> <p>26</p> <p><b>Note:</b> DIN-rail mounting is also possible. Refer to page 34 for supporting DIN-rails.</p>   |
| <p>PYFZ-14</p>   |  <p>Two, 4.2 x 5 mounting holes</p> <p>14-M3 x 8</p>                          |    |  <p>Two, M3, M4, or 4.5-dia. holes</p> <p>59±0.3</p> <p>22±0.2</p> <p>(TOP VIEW)</p> <p><b>Note:</b> DIN-rail mounting is also possible. Refer to page 34 for supporting DIN-rails.</p>  |

| Socket  | Dimensions  | Terminal arrangement/<br>Internal connections (top view)/<br>mounting holes          |
|---|---|--|
| <p>PYF14-ESN-B</p>   |   |   |
| <p>PYC-35-B</p>      |   |   |
| <p>PYF14-ESS-B</p>  |  |  |
| <p>PYC-35-B</p>    |  |  |

| Socket  | Dimensions  | Terminal arrangement/<br>Internal connections (top view)                             | Mounting holes  |
|---|---|--|---|
| <p>PY08/PY08-Y1</p>             | <p>(See note) Eight, 3 x 1.2 elliptical holes</p>  <p><b>Note:</b> The PY08-Y1 includes sections indicated by dotted lines.</p>      |  |    |
| <p>PY08QN/<br/>PY08QN-Y1</p>    | <p>(See note)</p>  <p><b>Note:</b> The PY08QN-Y1 includes sections indicated by dotted lines.</p>                                    |    |   |
| <p>PY08-02</p>                 |   |  |   |
| <p>PY14/PY14-Y1</p>           | <p>(See note) Fourteen, 3 x 1.2 elliptical holes</p>  <p><b>Note:</b> The PY14-Y1 includes sections indicated by dotted lines.</p> |  |  |
| <p>PY14QN/<br/>PY14QN-Y1</p>  | <p>(See note)</p>  <p><b>Note:</b> The PY14QN-Y1 includes sections indicated by dotted lines.</p>                                  |  |   |
| <p>PY14-02</p>               |    |  |  |

**Note:** Use a panel with plate thickness of 1 to 2 mm for mounting the Sockets.

**Short Bars for Relay Sockets and PYFZ/PYF Sockets**

**Short Bars for crossover wiring within one Socket or between Sockets**

| Application                    | Pitch   | Applicable model | Appearance and dimensions (mm) | L (Length) | No. of poles | Model #        | Specifications                                |
|--------------------------------|---------|------------------|--------------------------------|------------|--------------|----------------|---|
| For Contact terminals (common) | 7.75 mm | PYF-□-PU         |                                | 15.1       | 2            | PYDN-7.75-020□ | Max. carry current: 20 A<br>Minimum order: 10 |
|                                |         |                  |                                | 22.85      | 3            | PYDN-7.75-030□ |   |
|                                |         |                  |                                | 30.6       | 4            | PYDN-7.75-040□ |   |
|                                |         |                  |                                | 154.6      | 20           | PYDN-7.75-200□ |   |
| For Coil terminals             | 31.0 mm |                  |                                | 224.35     | 8            | PYDN-31.0-080□ |   |

\* Replace the box (□) in the model number with the specification code for the covering color. B: Black, S: Blue, R: Red

Note: When using short bar to coil terminals of PYF-□□-PU, make sure to use PYDN-31.0-080□ (31mm).

**Labels**

| Applicable sockets            | Model            | Manufacturer | Minimum order (Box) (quantity per box) |
|-------------------------------|------------------|--------------|--|
| PYF-08-PU(-L)<br>PYF-14PU(-L) | MG-CPM-04 41390N | Cembre       | 1,680<br>(35 sheet / 48 pieces)        |

Note: PRINTER: MARKINGENIUS MG3 (Ask to your Omron contact for more details on printers)

**Short Bars for within the Same Socket**

| Pitch | Applicable model | Appearance | Dimensions (mm) | No. of poles | Model #   | Specifications   |
|-------|------------------|------------|-----------------|--------------|-----------|--|
| 7 mm  | PYFZ-14          |            |                 | 2            | PYD-020B□ | Max. carry current: 20 A (18 A at 70°C)<br>Ambient operating temp.: -40 to 70°C (with no icing or condensation)<br>Ambient operating humidity: 45% to 85% (with no icing or condensation)<br>Conductor material: Brass<br>Conductor surface treatment: Nickel plating<br>Qty per package: 50/bag |
|       |                  |            |                 | 3            | PYD-030B□ |  |

\* Replace the box (□) in the model number with the specification code for the covering color. B: Black, Y: Yellow

**Short Bars for Adjacent Sockets**

| Pitch | Applicable model | Appearance | Dimensions (mm) | No. of poles | Model #   | Specifications   |
|-------|------------------|------------|-----------------|--------------|-----------|--|
| 22 mm | PYFZ-08          |            |                 | 2            | PYD-025B□ | Max. carry current: 20 A (18 A at 70°C)<br>Ambient operating temp.: -40 to 70°C (with no icing or condensation)<br>Ambient operating humidity: 45% to 85% (with no icing or condensation)<br>Conductor material: Brass<br>Conductor surface treatment: Nickel plating<br>Qty per package: 10/bag |
|       |                  |            |                 | 8            | PYD-085B□ |  |
| 29 mm | PYFZ-14          |            |                 | 2            | PYD-026B□ | Max. carry current: 20 A (18 A at 70°C)<br>Ambient operating temp.: -40 to 70°C (with no icing or condensation)<br>Ambient operating humidity: 45% to 85% (with no icing or condensation)<br>Conductor material: Brass<br>Conductor surface treatment: Nickel plating<br>Qty per package: 10/bag |
|       |                  |            |                 | 8            | PYD-086B□ |  |

\* Replace the box (□) in the model number with the specification code for the covering color. B: Black, S: Blue, R: Red


## Safety Precautions

### Maximum Carry Current


- Do not allow the total current for all shorted contact form to exceed the maximum carry current of the Short Bar.
- Do not exceed the maximum carry current of the relay contacts for individual contact form.
- If you use more than one Socket, use End Plates (PFP-M).

### Hold-down Clips

**PYC-A1**  
(2 pcs per set)



**PYC-E1**  
(2 pcs per set)




### For sockets PYF14-ESN/-ESS


| Model   | Description                                 |
|---------|---|
| PYC-0   | Metal spring clip (Used with Relay only)    |
| PYC 35  | Plastic holding clip (Used with Relay only) |
| PYC TR1 | Thermoplastic writable label                |

**Note:** For total dimensions with plastic clip please refer to drawings of the sockets.


**PYC-P**



**PYC-1**




**Y92H-3**




### Terminal Covers for PYFZ-08/PYFZ-14 Sockets

**PY CZ-C08**  
(for PYFZ-08)




**PY CZ-C14**  
(for PYFZ-14)




### Dimensions with terminal cover

(Unit: mm)

**PY CZ-C08**




**PY CZ-C14**






Mounting Plates for Back-connecting Sockets

PYP-1




t=1.6

PYP-18






PYP-36






DIN-rails and Accessories  
Supporting DIN-rails

PFP-50N/PFP-100N




Note: The figure in the parentheses is for PFP-50N.


PFP-100N2



End Plate  
PFP-M



Spacer  
PFP-S



# MY(S)

## Safety Precautions

---

Refer to the *Common Relay Precautions*.

Refer to *Products Related to Common Sockets and DIN Tracks* for precautions on the applicable Sockets.

Refer to *PYF-□□-PU/P2RF-□□-PU* for precautions on Push-In Plus Terminal Block Sockets.


### Precautions for Correct Use

#### Handling

For models with a built-in operation indicator, models with a built-in diode, or high-sensitivity models, check the coil polarity when wiring and wire all connections correctly (DC operation).

#### Installation

- There is no specifically required installation orientation, but make sure that the Relays are installed so that the contacts are not subjected to vibration or shock in their movement direction.



- Use two M3 screws to attach Flange-mounted models (MY□F) and tighten the screws securely (tightening torque: 0.98 N•m).

#### Using MY-series Relays with Microloads with Infrequent Operation

If any standard MY-series Relays (e.g., MY4) are used infrequently to switch microloads, the contacts may become unstable and eventually result in poor contact. In this case, we recommend using the MY4Z-CBG Series, which has high contact reliability for microloads (Refer to page 15.)

#### About the Built-in Diode and CR Elements

The diode or CR element that are built into the Relay are designed to absorb the reverse voltage from the Relay coil. If a large surge in voltage is applied to the diode or CR element from an external source, the element will be destroyed. If there is the possibility of large voltage surges that could be applied to the elements from an external source, take any necessary surge absorption measures.

#### Latching Levers

- Turn OFF the power supply when operating the latching lever. After you use the latching lever always return it to its original state.
- Do not use the latching lever as a switch.
- The latching lever can be used for 100 operations min.

#### Relay Replacement

To replace the Relay, turn OFF the power supply to the load and Relay coil sides to prevent unintended operation and possible electrical shock.

# Terms and Conditions Agreement

## **Read and understand this catalog.**

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

## **Warranties.**

- (a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.
- (b) Limitations. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE.

Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty.

See <http://www.omron.com/global/> or contact your Omron representative for published information.

## **Limitation on Liability; Etc.**

OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY.

Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.

## **Suitability of Use.**

Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT(S) IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

## **Programmable Products.**

Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.

## **Performance Data.**

Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.

## **Change in Specifications.**

Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.

## **Errors and Omissions.**

Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.

**Note: Do not use this document to operate the Unit.**

**OMRON Corporation Industrial Automation Company**

**Kyoto, JAPAN**

**Contact : [www.ia.omron.com](http://www.ia.omron.com)**

**Regional Headquarters**

**OMRON EUROPE B.V.**

Wegalaan 67-69, 2132 JD Hoofddorp  
The Netherlands

Tel: (31) 2356-81-300 Fax: (31) 2356-81-388

**OMRON ELECTRONICS LLC**

2895 Greenspoint Parkway, Suite 200  
Hoffman Estates, IL 60169 U.S.A.

Tel: (1) 847-843-7900 Fax: (1) 847-843-7787

**OMRON ASIA PACIFIC PTE. LTD.**  
438B Alexandra Road, #08-01/02 Alexandra  
Technopark, Singapore 119968  
Tel: (65) 6835-3011 Fax: (65) 6835-2711

Relais miniature

**OMRON (CHINA) CO., LTD.**  
Room 2211, Bank of China Tower,  
200 Yin Cheng Zhong Road,  
PuDong New Area, Shanghai, 200120, China  
Tel: (86) 21-5037-2222 Fax: (86) 21-5037-2200

**Authorized Distributor:**

©OMRON Corporation 2018-2023 All Rights Reserved.  
In the interest of product improvement,  
specifications are subject to change without notice.

**CSM\_1\_10**

**Cat. No. J224-E1-09** 0423 (1118)