

**Prise SCHUKO 16 A 250 V~
sans shutter**



Spécification	Réf.	UV.	EUR/pièce HTVA	SP	EAN
 blanc crème brillant	0466 01	10	5,26	21	4010337466017
 blanc brillant	0466 03	10	5,26	21	4010337466031
 blanc satiné	0466 27	10/100	5,26	21	4010337466277
 anthracite	0466 28	10/100	6,54	11	4010337466284
 teinte alu	0466 26	10/100	9,97	11	4010337466260
 noir mat	0466 005	10/100	9,96	11	4010337037644
 gris mat	0466 015	10/100	9,97	11	4010337081128
 acier inoxydable	0466 600	1/5	16,16	11	4010337034094
 chrome / blanc crème	0466 615	1/5	16,80	11	4010337001492



bronze / noir

0466 603

1/5

16,80

11

4010337097884



bronze / blanc crème

0466 613

1/5

16,80

11

4010337097914



laiton / noir

0466 604

1/5

16,80

11

4010337097891



laiton / blanc crème

0466 614

1/5

16,80

11

4010337097907



chrome / noir

0466 605

1/5

16,80

11

4010337001485

Caractéristiques techniques

Profondeur d'encastrement: 32 mm

section de raccordement
- Pour les conducteurs de: 1,5 mm² à 2,5 mm²

Indications

- Contrôlé selon T.N.O. avec pression de compression augmentée de l'étrier de mise à la terre