


## Wartel PG - "IPON" IP68 – Presse-étoupe PG



Geïntegreerde trekcontlasting.

Amarrage du câble intégré.

Behuizing: polyamide halogeen vrij.

Corps: polyamide libre d'halogène.

IP68 5bar

IP68 5bar

Brandklasse: UL49 V-O

Classement au feu: UL49 V-O

Gloeidraadtest: 850°C

Test du filament: 850°C

### RAL 7035 lichtgrijs - gris claire

PG	Ø Kabel - Câble	Gam.	Referentie - Référence	Verpakking - Emballage
7	3 - 6,5	28	1234P0701	50
9	4 - 8	28	1234P0901	50
11	5 - 10	28	1234P1101	50
13,5	6 - 12	28	1234P1301	50
16	9 - 14	28	1234P1601	50
21	12 - 18	28	1234P2101	25
29	17 - 25	28	1234P2901	10
36	20 - 32	28	1234P3601	10
42	32 - 38	28	1234P4201	5
48	37 - 44	28	1234P4801	5

### RAL 7035 donkergrijs - gris foncé

PG	Ø Kabel - Câble	Gam.	Referentie - Référence	Verpakking - Emballage
7	3 - 6,5	28	1234P0702	50
9	4 - 8	28	1234P0902	50
11	5 - 10	28	1234P1102	50
13,5	6 - 12	28	1234P1302	50
16	9 - 14	28	1234P1602	50
21	12 - 18	28	1234P2102	25
29	17 - 25	28	1234P2902	10
36	20 - 32	28	1234P3602	10
42	32 - 38	28	1234P4202	5
48	37 - 44	28	1234P4802	5

### RAL 9005 zwart - noir

PG	Ø Kabel - Câble	Gam.	Referentie - Référence	Verpakking - Emballage
7	3 - 6,5	28	1234P0703	50
9	4 - 8	28	1234P0903	50
11	5 - 10	28	1234P1103	50
13,5	6 - 12	28	1234P1303	50
16	9 - 14	28	1234P1603	50
21	12 - 18	28	1234P2103	25
29	17 - 25	28	1234P2903	10
36	20 - 32	28	1234P3603	10
42	32 - 38	28	1234P4203	5
48	37 - 44	28	1234P4803	5