



IE FC RJ45 PLUG 180 2X2,
RJ45 PLUG CONNECTOR (10/100MBIT/S) W. RUGGED
METAL HOUSING AND FC CONNECTING METHOD,
FOR IE FC CABLE 2X2 180 DGR CABLE OUTLET 1 PACK
= 1 PCS

Transfer rate

- 1 / for Industrial Ethernet 10 Mbit/s
- 2 / for Industrial Ethernet 100 Mbit/s

Interfaces

| | |
|---|-----|
| Number of electrical connections | |
| <ul style="list-style-type: none"> • for Industrial Ethernet FC TP cables 4 • for network components and terminal equipment 1 | |
| Design of the electrical connection | |
| <ul style="list-style-type: none"> • for network components and terminal equipment RJ45 connector | |
| Design of the electrical connection / FastConnect | Yes |

Mechanical data

| | |
|-----------------------------|-------|
| Material / of the enclosure | metal |
|-----------------------------|-------|

Design, dimensions and weight

| | |
|------------|---------|
| Width | 13.7 mm |
| Height | 16 mm |
| Depth | 55 mm |
| Net weight | 35 g |

Permitted ambient conditions

| | |
|--|--|
| Ambient temperature | |
| <ul style="list-style-type: none"> • during operating -40 ... +85 °C • during storage -40 ... +85 °C | |

| | |
|--|----------------|
| • during transport | -40 ... +85 °C |
| Relative humidity / at 25 °C / without condensation / during operating / maximum | 95 % |
| Protection class IP | IP20 |
| Product properties, functions, components / general | |
| Product feature / [not supplied - silicon-free] | Yes |
| Product component | |
| • strain relief | Yes |
| Standards, specifications, approvals | |
| Verification of suitability | |
| • RoHS conformity | Yes |
| • UL-registration | Yes |
| Standard for structured cabling | Cat5 |
| letzte Änderung: | May 20, 2013 |