

M6/8.P

General Information

Extended Product Type:	M6/8.P
Product ID:	1SNA165114R1700
EAN:	3472591651140
Catalog Description:	M6/8.P
Long Description:	Blocs vissés pour conducteur de protection Les blocs vissés pour conducteur de protection ABB Entrelec permettent le raccordement des conducteurs de protection terre sur le rail DIN. Application: tout circuit électrique monté en armoire ou coffret Circuits de protection Avantages: Compatibilité avec les blocs de liaison équivalents: pas de déclassement en tension Identification aisée grâce au code couleur "vert jaune" des supports isolants des blocs Flexibilité: 2 Versions sont disponibles bloc terre relié au profilé (support isolant vert-jaune) bloc terre non relié au profilé (support isolant jaune avec marquage vert sur le dessus) Caractéristiques: Supportent un courant de court-circuit de 120A/mm ² pendant 1 seconde Section de raccordement de 2.5mm ² à 95 mm ² conforme à la norme CEI 60947-7-2

Categories

Products » Produits basse tension » Raccordement » Blocs de jonction » Blocs de jonction vissés

Ordering

EAN:	3472591651140
Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Weight:	26 g
----------------------------	------

Container Information

Package Level 1 Units:	50 piece
Package Level 1 Width:	81 mm
Package Level 1 Height:	47 mm
Package Level 1 Length:	220 mm
Package Level 1 Gross Weight:	1.3 kg
Package Level 1 EAN:	3472591651140
Package Level 2 Units:	750 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	150 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	19.85 kg
Product Packing Type:	Box

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

Technical UL/CSA

Flammability According to UL94:	V0
--	----

Additional Information

Color:	vert/jaune
Connection Type:	Screw clamp
Function:	Protection
Gauge(s) of Form:	A5
IIT Publishing Status:	Level 0 - Information enabled
Product Main Type:	M6/8.P
Product Name:	Terminal block

Rated Cross-Section:	6 mm ²
Recommended Screw Driver:	4 mm
Spacing:	8 mm
Sub-Function:	conducteur de protection relié au profilé
Tightening Torques:	acc. IEC 60947-1 0.8 N·m Manufacturer 1 N·m
Wire Stripping Length:	12 mm

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225004C1000
GOST Certificate:	1SND161005A1103

Classifications

E-nummer:	E2925526
Object Classification Code:	X
