

BELGIUM



Close Window


[→ See all Eaton Ellipse ECO UPS Documentation](#)[→ Back to Family Page](#)**EL500FR**

Eaton Ellipse ECO 500 FR



General

Configuration	Rack/Tower
Part Number	EL500FR
Color	Black
Rating (VA/Watts)	500/300
Dimensions (H x W x D, mm)	263 x 81 x 235
Weight (kg)	2.9
Warranty	2 years warranty, Standard product exchange, including the battery ; warranty for the connected computing equipment for an unlimited amount (EU countries)

Electrical Input

Connection	(1) IEC-320-C14
	
Input Voltage Range	184 V - 264 V (adjustable to 161 V - 284 V)
Protection	Resettable circuit breaker
Nominal Voltage	230 V
Operating Frequency	50-60 Hz autoselect

Electrical Output

Voltages	230 V (adjustable to 220 V, 230 V, 240 V)
Output Receptacles	(3) French (1) French surge only
	 

Battery

Battery Type	Replaceable sealed lead acid
Battery Replacement Indicators	LED + audible alarm

Battery Test	Yes (Automatic)
Cold start (No mains power)	Yes
Deep Discharge Protection	4 hours

Environmental & Standards

Surge Protection	Surge protection device compliant with IEC 61643-1
Performance - Safety - EMC	IEC 62040-1, IEC 60950-1, IEC 62040-2, CB Report, CE mark
Data Line Protection	Tel/Fax/Modem/Internet and Ethernet



Copyright ©2012 Eaton Corporation. All rights reserved.