



TERMINAL BLOCK HOUSING

RKK 4/10-10x4²



RKK 4/10-10x4²

Terminal block housing

CUSTOMIZABLE

94 x 94 x 57 mm
Article number: 60740401

Terminal block housing, flat design, Polystyrene, grey, similar to RAL 7035, equipped with 10-pole terminal block 0.2-4 mm² (screw connection), incl. 4 attachment bushes M20, seal range 8 - 13.5 mm, IP54



Technical data

Measures

Width:	94 mm
Length:	94 mm
Height:	57 mm

Material

Base:	Polystyrene, grey, similar to RAL 7035
Cover:	Polystyrene, grey, similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Other attributes

Ingress protection:	IP66/IP54 - acc.
---------------------	------------------

Accessory

TK ABL
ASS-kl
KS M20



TERMINAL BLOCK HOUSING

RKK 4/10-10x4²

EN60529 / DIN
VDE 0470-1

Impact resistance: IK07 acc. DIN EN
5012 / VDE 0470
Part 100

Protection class: II - isolate
protection acc.
VDE 0106

Heavy metals-free: Yes

PVC-free: Yes

Silicone-free: Yes

Weatherproof: No

Combustion behaviour to UL: HB acc. UL94

Combustion behaviour to VDE: 650°C acc. VDE
0471/ EN 60695

Fitted for outdoor application: No

Knockouts: Yes

Equipment: screw terminal

Number terminals: 1 Quantity

Number of clamping points: 10

Rated cross section: 4 mm²

Environmental attributes

Ambient temperature (min.): -25 °C

Ambient temperature (max.): 40 °C

Ambient temperature (24 h): 35 °C

Max. rel. humidity at 25° C (short
Therm): 95%

Max. rel. humidity at 40° C: 50%

RKK 4/10-10x4² Boîtier pour bornes