



EMPTY ENCLOSURE

# TK PC 77-6-m



## TK PC 77-6-m

Empty enclosure

**CUSTOMIZABLE**

65 x 65 x 57 mm  
Article number: 12740101

Empty enclosure - Industrial Quality -, base and cover: glass fibre reinforced polycarbonate, grey, similar to RAL 7035

with metric knockouts



## Technical data

### Measures

Width:	65 mm
Length:	65 mm
Height:	57 mm
Inner height:	45 mm

### Material

Base:	Polycarbonate, glass-fibre reinforced, grey similar to RAL 7035
Cover:	Polycarbonate, glass-fibre reinforced, grey similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass

## Certificates



## Accessory

TK MPI-77

TS 15-49,5

ASS-kl

HBA

TK ABL

TK DST



EMPTY ENCLOSURE

# TK PC 77-6-m

reinforced

## Other attributes

Ingress protection:	IP66 - acc. EN 60529 / DIN VDE 0470-1
Impact resistance:	IK08 acc. DIN EN 5012 / VDE 0470 segment 100
Protection class:	II - isolate protection acc. VDE 0106
Rated insulation voltage AC:	690V V
Rated insulation voltage DC:	1000 V
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Fitted for outdoor application:	Yes
Weatherproof:	Yes
Combustion behaviour to UL:	V-2 acc. UL 94
Combustion behaviour to VDE:	960°C acc. VDE 0471/ EN 60695
sealable:	Yes
Knockouts:	Yes

## Environmental attributes

Ambient temperature (min.):	-35 °C
Ambient temperature (max.):	80 °C
Ambient temperature (24 h):	60 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%