



TERMINAL BLOCK HOUSING

RKK 4/18-18x4²

RKK 4/18-18x4²

Terminal block housing

CUSTOMIZABLE

180 x 94 x 57 mm
Article number: 60041801

Terminal block housing, flat design, Polystyrene, grey, similar to RAL 7035, equipped with 18-pole terminal block 0.2-4 mm² (screw connection), incl. 6 attachment bushes M20, seal range 8 - 13.5 mm, IP54



Technical data

Measures

Width:	180 mm
Length:	94 mm
Height:	57 mm

Material

Base:	Polystyrene
Cover:	Polystyrene
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Other attributes

Ingress protection:	IP66/IP54 - acc. EN60529 / DIN VDE 0470-1
Impact resistance:	IK07 acc. DIN EN

Accessory

TK ABL

ASS-kl

HBA

KS M20



TERMINAL BLOCK HOUSING

RKK 4/18-18x4²

5012 / VDE 0470
Part 100

Protection class: II - isolate protection acc. VDE 0106

Heavy metals-free: Yes

PVC-free: Yes

Silicone-free: Yes

Weatherproof: No

Combustion behaviour to UL: HB acc. UL94

Combustion behaviour to VDE: 650°C acc. VDE 0471/ EN 60695

Knockouts: Yes

Equipment: screw terminal

Number terminals: 1 Quantity

Number of clamping points: 18

Rated cross section: 4 mm²

Environmental attributes

Ambient temperature (min.): -25 °C

Ambient temperature (max.): 40 °C

Ambient temperature (24 h): 35 °C

Max. rel. humidity at 25° C (short Therm): 95%

Max. rel. humidity at 40° C: 50%