	19 34 115 □ C€ IP 20	19 34 115 E CE IP 20
Reference	12403730	12400730
Dimensions (LxWxH)	115x34x19	115x34x19
Input	220-240V 50/60Hz	220-240V 50/60Hz
Ambient temperature	-25°C to +45°C	-25°C to +45°C
Power factor (max)	0.54	0.54
Dimming	-	-
Max drivers on MCB 16A type B	27	27
	350mA / 15W	500mA / 12W
Output	1-43V DC	1-24V DC
Cake 48 IP55 LED GE	14	8
Chapeau 206 LED GE	2	1
Duell recessed 1x LED GE	2	1
Duell recessed 2x LED GE	1	
Ex-L low 158 LED GE Grib LED GE	1 4	
Hipy 110 IP67 LED GE Hipy 70 IP67 LED GE	2 1	1 🔨
Intro 89 IP44 GE	2	1
Julien IP54 LED GE	4	· · · · · · · · · · · · · · · · · · ·
K-0 80 LED GE	2	1
K-1 89 LED GE	2	1
Kurk IP40 LED GE	2	1
Kurk surface IP40 LED GE	2	1
Lotis 48 IP55 LED GE	14	8
Lotis 82 IP55 LED GE	2	1
Lotis 82 LED GE	2	1
Lotis 97 adjustable LED GE	2	1
Marty LED GE	14	
Mini a(r)mor LED GE	14	
Mini multiple 1x LED GE	2	1
Mini multiple 2x LED GE	1	
Mini multiple 3x LED GE		
Mini multiple 4x LED GE		
M-LED 111 GE Nomad 2x LED GE	1	
Nomad 2x LED GE Nomad 4x LED GE	1	
Rektor recessed LED GE	1	
Scotty 270 adjustable LED GE	1	
Scotty 270 LED GE	1	
Slide square clockwork LED GE	2	1
Slide square IP44 LED GE	2	1
Slide square LED GE	2	1
Slide twin LED GE	1	
Smart cake 115 adjustable LED GE	2	1
Smart cake 115 LED GE	1	
Smart cake 82 LED GE	2	1
Smart kup 115 adjustable LED GE	2	1
Smart kup 115 LED GE	1	
Smart kup 82 LED GE	2	1
Smart lotis 115 adjustable LED GE	2	1
Smart lotis 115 LED GE	1	
Smart lotis 82 LED GE	2	1
Stove LED GE	2	1

⚠ driver does not fit through cutout hole of fixture