



WEVER & DUCRÉ
LIGHTING

DEEP 1.0 PAR16

112120B0

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling
 Recessed
 Jet Black
 IP20
 Interior
 445 lm
 RAL 9005^a

LED

Lamp PAR16
 PAR16
 Socket GU10
 max. 12 W
 CRI 90

OPTICAL

Wide Flood
 Beam angle 48°

PHYSICAL

Diameter 84 mm
 Height 102 mm
 0.29 kg
 wire springs



ELECTRICAL

100 - 240 V
 LED Inset 6.5 W
 Class 2
 Safety distance 0.3 m


CUTOUT

Diameter 76-79 mm
 Min. ceiling thickness 4 mm
 Max. ceiling thickness 27 mm
 Recessed depth 105 mm

^a Color may deviate slightly due to production conditions.



LIGHT DISTRIBUTION



[112120B0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
 © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

DEEP 1.0 PAR16

112120B0

CONE DIAGRAM

wide flood 48°

h (m)	EO ² (lx)	ø (m)
1	623	0.89
2	156	1.78
3	69	2.67
4	39	3.56
5	25	4.45

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50-58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50-58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50-58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50-52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50-52	9 0 5 2 2 7 S 4