



**WEVER & DUCRÉ**  
LIGHTING

# RAY

## WALL mini 2.0

301220W0

Project

Type

Notes

Quantity

Date

### GENERAL

Wall  
Surface  
Signal White  
IP20  
Interior  
Indirect 450<sup>a</sup> to 455<sup>b</sup> lm  
Direct 450<sup>a</sup> to 455<sup>b</sup> lm  
Total 900<sup>a</sup> to 910<sup>b</sup> lm  
RAL 9003<sup>c</sup>

### LED

Lamp 2 x PAR16  
PAR16  
Socket GU10  
max. 12 W  
CRI  $\geq$  80

### OPTICAL

Beam angle 360°  
UGR < 13  
65° < 3000 cd/m<sup>2</sup>

### PHYSICAL

Diameter 67 mm  
Height 200 mm  
0.36 kg


### ELECTRICAL

100 - 240 V  
Total connected power 13.2<sup>b</sup> to 13.3<sup>a</sup> W  
Class 1  
Safety distance 0.3 m


<sup>a</sup> LED 3000K CRI 80 white

<sup>b</sup> LED 2700K CRI 80 white


<sup>c</sup> Color may deviate slightly due to production conditions.



Cylindrical wall surface mounted luminaire made from aluminium; surface Signal White; powder coated; matt texture; RAL 9003; direct/indirect light distribution; lamp socket GU10; lamp type PAR16; 2x max. 12W; 100 - 240 V; lamp not included; degree of protection IP20; PC1;



### LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# RAY

## WALL mini 2.0

301220W0

### LAMPS

#### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	∅50·58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	∅50·58	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	∅50·58	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	∅50·58	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	∅50·52	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	∅50·52	9 0 5 2 2 7 S 4