

Insulated screwdrivers

According to IEC 60900:2004, classification VDE 0682, part 201.

Individual tested in water bath with a testing voltage of 10.000 Volt.

Electricians screwdrivers

According to DIN 7437

2,5 x 0,4	75	160	12	11 7701
3,0 x 0,5	100	185	12	11 7702
3,5 x 0,6	100	185	12	11 7703
4,0 x 0,8	100	185	12	11 7704
5,5 x 1,0	125	220	12	11 7705
6,5 x 1,2	150	245	12	11 7706
8,0 x 1,2	175	285	12	11 7708
10,0 x 1,6	200	310	12	11 7710

Crosshead screwdrivers Phillips

According to DIN 7438

PH 0	60	145	12	11 7730
PH 1	80	165	12	11 7731
PH 2	100	195	12	11 7732
PH 3	150	260	12	11 7733

Crosshead screwdrivers Pozidriv

PZ 0	60	145	12	11 7740
PZ 1	80	165	12	11 7741
PZ 2	100	195	12	11 7742
PZ 3	150	260	12	11 7743

Special screwdrivers with combination-profile

For combined slotted/recessed head screws in electrical installations, i.e. terminal blocks

PZ 1	80	165	12	11 7751
PZ 2	100	195	12	11 7752
Set PZ1 and PZ2 (No. 11 7751 and 11 7752)			1	11 7750

Hexagon socket head wrench (Allen wrench)

According to DIN 7439

SW 3	75	160	12	11 7823
SW 4	75	160	12	11 7824
SW 5	75	170	12	11 7825
SW 6	100	195	12	11 7826
SW 8	100	210	12	11 7828

TORX®-Screwdrivers

T 8	60	145	12	11 7908
T 9	60	145	12	11 7909
T 10	60	155	12	11 7910
T 15	75	170	12	11 7915
T 20	100	195	12	11 7920
T 25	100	195	12	11 7925
T 30	100	210	12	11 7930

Socket wrench

According to DIN 7445

SW 5,5	125	220	12	11 7805
SW 6	125	220	12	11 7806
SW 7	125	235	12	11 7807
SW 8	125	235	12	11 7808
SW 9	125	235	12	11 7809
SW 10	125	235	12	11 7810
SW 11	125	235	12	11 7811
SW 13	125	235	12	11 7813