

Hulsuitdrijvers

RöhM

Uitdrijfspiëën - Type 266

Bestelnr.	Voor morse konus	Lengte mm
01.08.65.01		90
01.08.66.02	1 + 2	140
01.08.67.03	3	190
01.08.68.04	4	225
01.08.69.05	5 + 6	265
01.08.70.06	1-3	320
01.08.71.07	4 - 6	380



Verlenghulzen

RöhM

VLH

DIN 2187

Opmerking:

- Type 265: uitwendig geslepen
- Type 275: geheel gehard, inwendig en uitwendig geslepen

Bestelnr.	Morse konus binnen	Morse konus buiten	Lengte mm
Type 265 - Standaard			
01.08.44.77	1	1	145
01.08.45.78	2	1	160
01.08.46.79	1	3	175
01.08.47.80	1	4	200
01.08.48.81	1	5	232
01.08.49.82	1	2	160
01.08.50.83	2	2	175
01.08.51.84	2	3	194
01.08.52.85	2	4	215
01.08.53.86	2	5	247
01.08.54.87	3	2	196
01.08.55.88	3	3	215
01.08.56.89	3	4	240
01.08.57.90	3	5	268
01.08.58.91	4	3	240
01.08.59.92	4	4	265
01.08.60.93	4	5	300
01.08.61.94	4	6	355
01.08.62.95	5	4	300
01.08.63.96	5	5	335
01.08.64.00	5	6	390
Type 275 - Precisie			
21.63.52.42	1	1	145
21.63.53.43	2	1	160
21.63.54.44	1	2	160
21.63.55.45	2	2	175
21.63.56.46	3	2	196
21.63.57.47	1	3	175
21.63.58.48	2	3	194
21.63.59.49	3	3	215
21.63.60.50	4	3	240
21.63.61.51	1	4	200





Bestelnr.	Morse konus binnen	Morse konus buiten	Lengte mm
21.63.62.52	2	4	215
21.63.63.53	3	4	240
21.63.64.54	4	4	265
21.63.65.55	5	4	300
21.63.66.56	1	5	232
21.63.67.57	2	5	247
21.63.68.58	3	5	268
21.63.69.59	4	5	300
21.63.70.60	5	5	335
21.63.71.61	4	6	355
21.63.72.62	5	6	390

BV

Opmerking:

- Type 268: uitwendig geslepen
- Type 278: geheel gehard, inwendig en uitwendig geslepen

Bestelnr.	Morse konus binnen	Morse konus buiten	Lengte mm
Type 268 - Standaard			
07.98.83.52	1	1	200
07.98.84.53	1	1	250
07.98.85.54	1	1	300
21.63.14.04	1	1	350
21.63.15.05	1	1	400
21.63.16.06	1	1	450
21.63.17.07	1	1	500
07.98.81.50	2	2	300
07.98.86.55	2	2	200
07.98.87.56	2	2	250
21.63.18.08	2	2	350
21.63.19.09	2	2	400
21.63.20.10	2	2	450
21.63.21.11	2	2	500
21.63.22.12	2	2	600
07.98.82.51	3	3	250
07.98.80.49	3	3	300
07.98.88.57	3	3	350
21.63.23.13	3	3	400
21.63.24.14	3	3	450
21.63.25.15	3	3	500
21.63.26.16	3	3	600
07.98.89.58	4	4	300
07.98.90.59	4	4	350
07.98.91.60	4	4	400
21.63.27.17	4	4	450
21.63.28.18	4	4	500
21.63.29.19	4	4	600
Type 278 - Precisie			
21.62.26.13	1	1	200
21.62.27.14	1	1	250
21.62.28.15	1	1	300
21.62.29.16	1	1	350
21.62.30.17	1	1	400
21.62.31.18	1	1	450
21.62.32.19	1	1	500
21.62.33.20	2	2	200
21.62.34.21	2	2	250
21.62.35.22	2	2	300
21.62.36.23	2	2	350
21.62.37.24	2	2	400
21.62.38.25	2	2	450

Bestelnr.	Morse konus binnen	Morse konus buiten	Lengte mm
21.62.39.26	2	2	500
21.62.40.27	2	2	600
21.62.41.28	3	3	250
21.62.42.29	3	3	300
21.62.43.30	3	3	350
21.62.44.31	3	3	400
21.62.45.32	3	3	450
21.62.46.33	3	3	500
21.62.47.34	3	3	600
21.62.48.35	4	4	300
21.62.49.36	4	4	350
21.62.50.37	4	4	400
21.62.51.38	4	4	450
21.62.52.39	4	4	500
21.62.53.40	4	4	600

Verloophulzen

Röhm

RH

DIN 2185

Opmerking:

- Type 261: uitwendig geslepen
- Type 262: geheel gehard, inwendig en uitwendig geslepen

Bestelnr.	Morse konus binnen	Morse konus buiten	Lengte mm
Type 261 - Standaard			
01.08.00.33		1	80
01.08.01.34	1	2	92
01.08.02.35	2	3	112
01.08.03.36	1	3	99
01.08.04.37	3	4	140
01.08.05.38	2	4	124
01.08.06.39	1	4	124
01.08.07.40	4	5	171
01.08.08.41	3	5	156
01.08.09.42	2	5	156
01.08.10.43	1	5	156
01.08.11.44	5	6	218
01.08.12.45	4	6	218
01.08.13.46	3	6	218
01.08.14.47	2	6	218
Type 262 - Precisie			
38.17.34.39		1	80
38.17.35.40	1	2	92
14.05.88.35	2	3	112
38.17.36.41	1	3	99
38.17.40.45	3	4	140
38.17.39.44	2	4	124
38.17.38.43	1	4	124
38.17.44.49	4	5	171
38.17.43.48	3	5	156
38.17.42.47	2	5	156
38.17.41.46	1	5	156
38.17.48.53	5	6	218
38.17.47.52	4	6	218
38.17.46.51	3	6	218
38.17.45.50	2	6	218

