

Mèches HSS-Co - emmanchement Weldon 19 mm

Cobalt 8%

Remarque:

- Profondeur de perçage 30 mm: type de mèche IBS
- Profondeur de perçage 55 mm: type de mèche IBL

Ø mm	N° de Cde bij profondeur de perçage	
	30mm	55mm
12	18.66.45.17	62.70.99.91
13	10.71.83.95	08.21.56.94
14	10.73.42.60	06.20.24.41
15	06.20.33.50	06.20.36.53
16	10.73.68.86	06.20.29.46
17	06.20.41.58	08.21.57.95
18	10.73.80.01	06.20.25.42
19	06.20.42.59	06.20.37.54
20	10.73.89.10	06.20.27.44
21	06.20.34.51	08.21.55.93
22	10.74.05.26	06.20.30.47
23	06.20.43.60	08.21.58.96
24	06.20.23.40	18.67.09.81
25	06.20.44.61	18.67.10.82
26	10.74.11.32	08.21.51.89
27	06.20.26.43	08.21.59.00
28	10.74.19.40	06.20.28.45
29	06.20.35.52	18.67.11.83
30	06.20.31.48	08.21.60.01
31	06.20.38.55	18.67.12.84
32	10.73.37.55	08.21.50.88
33	06.20.39.56	18.67.13.85
34	06.20.32.49	18.67.14.86
35	08.21.62.03	18.67.15.87
36	06.20.40.57	08.21.61.02
37	18.66.46.18	18.67.16.88
38	18.66.47.19	18.67.17.89
39	18.66.48.20	18.67.18.90
40	18.66.49.21	18.67.19.91
41	08.21.52.90	18.67.20.92
42	18.66.50.22	18.67.21.93
43	18.66.51.23	18.67.22.94
44	18.66.52.24	18.67.23.95
45	18.66.53.25	18.67.24.96
46	18.66.54.26	18.67.25.00
47	18.66.55.27	18.67.26.01
48	18.66.56.28	18.67.27.02
49	18.66.57.29	18.67.28.03
50	18.66.58.30	18.67.29.04
51	18.66.59.31	18.67.30.05
52	18.66.60.32	18.67.31.06
53	18.66.61.33	18.67.32.07
54	18.66.62.34	18.67.33.08
55	18.66.63.35	18.67.34.09
56	18.66.64.36	18.67.35.10
57	18.66.65.37	18.67.36.11
58	18.66.66.38	18.67.37.12
59	18.66.67.39	18.67.38.13
60	18.66.68.40	18.67.39.14

