



## HSCo foret - Queue cylindrique



DIN 338 - Type GU500DZ

- Coupe à droite
- Résistance à l'usure
- Affûtage en pentes
- Angle d'affûtage: 118°
- **Application:** Applications universelles, acier allié ou non allié jusqu'à 800 N/mm<sup>2</sup>, non ferreux, fonte, plastiques

Ø mm	L mm	L de coupe mm	N° de Cde Exécution	
			N° 5523 Poli	N° 5519 Revêtement TiN
1,00	34	12	26.40.23.86	26.38.11.68
1,10	36	14	26.40.24.87	26.38.12.69
1,20	38	16	26.40.25.88	26.38.13.70
1,30	38	16	26.40.26.89	26.38.14.71
1,40	40	18	26.40.27.90	26.38.15.72
1,50	40	18	26.40.28.91	26.38.16.73
1,60	43	20	26.40.29.92	26.38.17.74
1,70	43	20	26.40.30.93	26.38.18.75
1,80	46	22	26.40.31.94	26.38.19.76
1,90	46	22	26.40.32.95	26.38.20.77
2,00	49	24	26.40.44.10	26.38.32.89
2,10	49	24	26.40.45.11	26.38.33.90
2,20	53	27	26.40.46.12	26.38.34.91
2,30	53	27	26.40.47.13	26.38.35.92
2,40	57	30	26.40.49.15	26.38.37.94
2,50	57	30	26.40.50.16	26.38.38.95
2,60	57	30	26.40.51.17	26.38.39.96
2,70	61	33	26.40.52.18	26.38.40.00
2,80	61	33	26.40.54.20	26.38.42.02
2,90	61	33	26.40.55.21	26.38.43.03
3,00	61	33	00.93.79.67	26.38.44.04
3,10	65	36	26.40.57.23	26.38.45.05
3,20	65	36	26.40.59.25	26.38.47.07
3,30	65	36	26.40.60.26	26.38.48.08
3,40	70	39	26.40.61.27	26.38.49.09
3,50	70	39	00.93.81.69	26.38.50.10
3,60	70	39	26.40.64.30	26.38.52.12
3,70	70	39	26.40.65.31	26.38.53.13
3,80	75	43	26.40.66.32	26.38.54.14
3,90	75	43	26.40.67.33	26.38.55.15
4,00	75	43	00.93.82.70	26.38.57.17
4,10	75	43	26.40.70.36	26.38.58.18
4,20	75	43	26.40.71.37	26.38.59.19
4,30	80	47	26.40.72.38	26.38.60.20
4,40	80	47	26.40.74.40	26.38.62.22
4,50	80	47	26.40.75.41	26.38.63.23
4,60	80	47	26.40.76.42	26.38.64.24
4,70	80	47	26.40.77.43	26.38.65.25
4,80	86	52	26.40.79.45	26.38.67.27
4,90	86	52	26.40.80.46	26.38.68.28
5,00	86	52	26.40.81.47	26.38.69.29
5,10	86	52	26.40.82.48	26.38.70.30
5,20	86	52	26.40.84.50	26.38.72.32
5,30	86	52	26.40.85.51	26.38.73.33
5,40	93	57	26.40.86.52	26.38.74.34
5,50	93	57	26.40.87.53	26.38.75.35
5,60	93	57	26.40.89.55	26.38.77.37
5,70	93	57	26.40.90.56	26.38.78.38
5,80	93	57	26.40.91.57	26.38.79.39
5,90	93	57	26.40.92.58	26.38.80.40
6,00	93	57	26.40.94.60	26.38.82.42
6,10	101	63	26.40.95.61	26.38.83.43

Ø mm	L mm	L de coupe mm	N° de Cde Exécution	
			N° 5523 Poli	N° 5519 Revêtement TiN
6,20	101	63	26.40.96.62	26.38.84.44
6,30	101	63	26.40.97.63	26.38.85.45
6,40	101	63	26.40.99.65	26.38.87.47
6,50	101	63	26.41.00.66	26.38.88.48
6,60	101	63	26.41.01.67	26.38.89.49
6,70	101	63	26.41.02.68	26.38.90.50
6,80	109	69	26.41.03.69	26.38.91.51
6,90	109	69	26.41.04.70	26.38.92.52
7,00	109	69	26.41.05.71	26.38.93.53
7,10	109	69	26.41.06.72	26.38.94.54
7,20	109	69	26.41.08.74	26.38.96.56
7,30	109	69	26.41.09.75	26.38.97.57
7,40	109	69	26.41.10.76	26.38.98.58
7,50	109	69	26.41.11.77	26.38.99.59
7,60	117	75	26.41.12.78	26.39.00.60
7,70	117	75	26.41.13.79	26.39.01.61
7,80	117	75	26.41.14.80	26.39.02.62
7,90	117	75	26.41.15.81	26.39.03.63
8,00	117	75	26.41.17.83	26.39.05.65
8,10	117	75	26.41.18.84	26.39.06.66
8,20	117	75	26.41.19.85	26.39.07.67
8,30	117	75	26.41.20.86	26.39.08.68
8,40	117	75	26.41.21.87	26.39.09.69
8,50	117	75	26.41.22.88	26.39.10.70
8,60	125	81	64.38.63.74	64.38.55.66
8,70	125	81	64.38.16.27	64.38.09.20
8,80	125	81	26.41.24.90	26.39.12.72
8,90	125	81	64.38.62.73	-
9,00	125	81	26.41.25.91	26.39.13.73
9,10	125	81	64.38.15.26	64.38.08.19
9,20	125	81	64.38.61.72	64.38.92.06
9,30	125	81	26.41.26.92	26.39.14.74
9,40	125	81	64.38.14.25	64.38.91.05
9,50	125	81	26.41.27.93	26.39.15.75
9,60	133	87	64.38.13.24	64.38.90.04
9,70	133	87	64.38.94.08	64.38.07.18
9,80	133	87	26.41.28.94	26.39.16.76
9,90	133	87	64.38.12.23	64.38.06.17
10,00	133	87	00.93.97.85	26.38.21.78
10,10	133	87	64.38.11.22	64.38.05.16
10,20	133	87	00.93.98.86	26.38.22.79
10,30	133	87	64.38.93.07	64.38.04.15
10,40	133	87	64.38.10.21	64.38.03.14
10,50	133	87	26.40.35.01	26.38.23.80
11,00	142	94	00.94.00.88	26.38.24.81
11,50	142	94	00.94.01.89	26.38.26.83
12,00	151	101	00.94.02.90	26.38.27.84
12,50	151	101	26.40.40.06	26.38.28.85
13,00	151	101	26.40.41.07	26.38.29.86
13,50	160	108	26.40.42.08	26.38.30.87
14,00	160	108	26.40.43.09	26.38.31.88