

Osborn

Brosses circulaires - fil ondulé

• Ø fil: 0,30 mm

Ø mm	Largeur mm	Longueur fil mm	Ø d'alésage mm	Vitesse max. tr/min	N° de Cde Exécution	
					acier	inox
Brosses circulaires - fil ondulé						
75	19	16	20	10000	01.27.24.17	01.27.32.25
100	20	23	20	8000	01.27.25.18	01.27.33.26
125	22	30	20	6000	01.27.26.19	01.27.34.27
150	30	29	31,75	6000	01.27.27.20	01.27.35.28
178	32	38	31,75	6000	01.27.28.21	01.27.36.29
200	30	38	31,75	4500	01.27.29.22	01.27.37.30
250	38	47	20 - 50,8	3600	01.27.30.23	53.26.99.72
300	32	50	25,4 - 50,8	3000	01.27.31.24	01.27.39.32

Brosses circulaires - fil ondulé ECO						
150	25	30	32	6000	63.65.03.86	-
200	25	42	32	4500	63.65.04.87	-

Ø 75-125 mm: Jeu d'adaptateurs 13 mm (1/2") et 16 mm (5/8")

Ø 150-200 mm: Jeu d'adaptateurs 13 mm (1/2"), 15 mm, 16 mm (5/8"), 19 mm, 20 mm, 7/8", 1"

Ø 250-300 mm: Veuillez spécifier le diamètre d'alésage



Brosses circulaires - fil ondulé

1 rang

• Ø fil: 0,30 mm

Ø mm	Largeur mm	Longueur fil mm	Ø d'alésage mm	Vitesse max. tr/min	N° de Cde Exécution	
					acier	inox
125	15	35	13	6000	08.35.38.21	-
125	18	35	13	6000	-	63.65.05.88
250	22	35	20	3600	08.35.36.19	53.26.73.46



Brosses coniques - fil ondulé

• Ø fil: 0,30 mm

Ø mm	Largeur mm	Longueur fil mm	Connexion	Vitesse max. tr/min	N° de Cde Exécution	
					acier	inox
Brosses coniques - fil ondulé						
100	10	20	M14x2,0	12500	01.27.40.33	-
100	20	20	M14x2,0	12500	01.27.41.34	01.27.42.35

Brosses coniques - fil ondulé ECO						
100	10	20	M14x2,0	12500	63.65.06.89	-



Brosses coniques - fil torsadé

• Ø fil: 0,50 mm

Ø mm	Largeur mm	Longueur fil mm	Connexion	Vitesse max. tr/min	N° de Cde Exécution	
					acier	inox
Brosses coniques - fil torsadé						
100	13	22	M14x2,0	12500	16.65.39.87	01.27.45.38
115	15	20	M14x2,0	12500	01.27.44.37	16.65.46.94

Brosses coniques - fil torsadé ECO						
100	13	20	M14x2,0	12500	63.65.07.90	-



Brosses coupes - fil ondulé

• Ø fil: 0,30 mm

Ø mm	Longueur fil mm	Connexion	Vitesse max. tr/min	N° de Cde Exécution	
				acier	inox
Brosses coupes - fil ondulé					
60	21	M14x2,0	12500	19.32.33.09	01.27.54.47
75	23	M14x2,0	12500	01.27.48.41	01.27.55.48
80	30	M14x2,0	8500	01.27.49.42	-
80	25	M14x2,0	8500	-	01.27.56.49
100	30	M14x2,0	8500	01.27.50.43	01.27.57.50
125	30	M14x2,0	8500	01.27.51.44	01.27.58.51
140	35	M14x2,0	8500	01.27.52.45*	01.27.59.52
150	40	M14x2,0	8500	01.27.53.46	-

Brosses coupes - fil ondulé ECO					
60	21	M14x2,0	12500	63.65.08.91	-
80	25	M14x2,0	8500	63.65.09.92	-

* Ø fil: 0,38 mm

