

Date

Name

Client

Project Name



Quote#

Type/Quantity

MINIGRID IN TRIMLESS 2 FRAME + 2 x MINIGRID SNAP-IN SOFT

202 73 02 + 2 x 202 790 81120

[Weblink](#)



Opening formaat:	KIT mm
Inbouwdiepte:	85 mm
Beschikbare kleuren:	ZWART + ZWART (202 73 02 B + 2 x 202 790 81120 B) WIT + WIT (202 73 02 W + 2 x 202 790 81120 W) ZWART + WIT (202 73 02 B + 2 x 202 790 81120 W) WIT + ZWART (202 73 02 W + 2 x 202 790 81120 B)

ADJUSTABLE 0° - 20°/350°
 INCL. 2 x POWERLED WHITE 10W / CRI>80 / 2700-1800K /850 lm
 INCL. 2 x REFLECTOR FL-33°
 EXCL. DIMMABLE LED POWER SUPPLY 650mA-DC

LED Technics:	Lichtbron: 1700 lm // 20 W // 85 lm/W Luminaire: 23 W // 0 lm/W
---------------	--

Klasse:	III
Gewicht:	0.9 KG
Protection level:	IP23/20
Minimumafstand:	n.v.t.

Opmerkingen:	Parts to be ordered separately.
--------------	---------------------------------

Benodigheden:	DIMMABLE LED POWER SUPPLY 650mA-DC MINIGRID IN 2 MOUNTING KIT MINIGRID IN 2 MOUNTING KIT LARGE CONCRETE PACK MGIT 2
---------------	--

Voor gedetailleerde installatie-instructies, raadpleeg de handleiding. [202_73_02_HAND.pdf](#)


MINIGRID IN TRIMLESS 2 FRAME + 2 x MINIGRID SNAP-IN SOFT

202 73 02 + 2 x 202 790 81120

Related references

LED VOEDINGEN

[Weblink / Specificatieblad](#)




LED POWER SUPPLY
650mA-DC DIM8
300 90 915 ED8
220-240V / 50-60Hz
Aantal toestellen: 0,5

Related references

BETON DOOS VOOR ZICHTBETON

[Weblink /
Specificatieblad](#)




CONCRETE PACK MGIT 2
202 71 96 02

Related references


MONTAGE KIT

[Weblink /
Specificatieblad](#)



MINIGRID IN 2 MOUNTING
KIT
202 71 95 02

[Weblink /
Specificatieblad](#)



MINIGRID IN 2 MOUNTING
KIT LARGE
202 71 95 02L

