




## 1.0 LED

LED 8W | 220-240VAC | 50-60Hz  
COB 2-step | incl. PS | phase-cut dim  
aluminium powder coated | brushed


CE 0.67kg TE 960° IP20  $\gamma$ 0,3  $\rho$  A36°



## 1.0 PAR16

PAR16 max. 50W | GU10  
220-240VAC | 50-60Hz  
aluminium powder coated | brushed

CE 0.66kg TE 960° IP20  $\gamma$ 0,9  $\rho$



	<b>146164W_</b>		<b>146120W0</b>
	<b>146164L_</b>		<b>146120L0</b>
	<b>146164G_</b>		<b>146120G0</b>
	<b>146164Q_</b>		<b>146120Q0</b>
	<b>146164P_</b>		<b>146120P0</b>
	<b>146164B_</b>		<b>146120B0</b>

### LIGHT COLOUR

2200K   >80CRI   315lm	<b>1</b>
2700K   >80CRI   480lm	<b>2</b>
3000K   >80CRI   480lm	<b>4</b>

### OPTIONAL

PAR16 LED GU10 6W phase-cut dim	<b>901228W2</b>
2700K 390lm	<b>901228W2</b>
3000K 410lm	<b>901228W4</b>
PAR16 LED GU10 7W ambient white dim	<b>901229S9</b>
1800-3000K	<b>901229S9</b>



### OPTIONAL

inner cover max. 10W

	<b>911011W1</b>
	<b>911011G1</b>
	<b>911011B1</b>








## 2.0 LED

2xLED8W | 220-240VAC | 50-60Hz  
COB 2-step | incl. PS | phase-cut dim  
aluminium powder coated | brushed


CE 1.17kg ⊕ 960° IP20 ⚡0,3⚡ P ⚡36°



## 2.0 PAR16

2xPAR16 max. 50W | GU10  
220-240VAC | 50-60Hz  
aluminium powder coated | brushed

CE 1.13kg ⊕ 960° IP20 ⚡0,9⚡



	146264W_
	146264L_
	146264G_
	146264Q_
	146264P_
	146264B_

	146220W0
	146220L0
	146220G0
	146220Q0
	146220P0
	146220B0

### LIGHT COLOUR

2200K | >80CRI | 2x315lm 1

2700K | >80CRI | 2x480lm 2

3000K | >80CRI | 2x480lm 4

### OPTIONAL

PAR16 LED GU10 6W phase-cut dim  
2700K 390lm 901228W2

3000K 410lm 901228W4

PAR16 LED GU10 7W ambient white dim  
1800-3000K 901229S9



### OPTIONAL

inner cover max. 10W

	911011W1
	911011G1
	911011B1

