

Connectors for copper cables

Branch circuit connectors for copper cables - KS series

General features

- copper alloy body
- bronze nut





Item code	Part number	Main cable		Branch cable		Coupling torque
		mm ²	Ø mm	mm ²	Ø mm	Nm
7601100	KS90	4 - 6	2.3 - 3.0	1.5 - 6	1.5 - 3.0	10
7601101	KS15	6 - 10	3.0 - 4.0	2.5 - 10	1.8 - 3.8	10
7601102	KS17	10 - 10	3.8 - 4.7	2.5 - 10	1.8 - 4.7	20
7601103	KS20	10 - 16	3.8 - 5.2	2.5 - 16	1.8 - 5.2	20
7601104	KS22	16 - 25	5.1 - 6.3	2.5 - 25	1.8 - 6.3	30
7601105	KS23	16 - 35	5.1 - 8.6	2.5 - 35	1.8 - 8.6	30
7601106	KS25	25 - 50	6.2 - 9.3	2.5 - 50	1.8 - 9.3	45
7601107	KS26	35 - 70	7.4 - 10.6	2.5 - 70	1.8 - 10.6	45
7601108	KS27	50 - 95	8.3 - 12.5	10 - 95	3.7 - 12.5	60
7601109	KS29	50 - 120	8.8 - 15.2	10 - 120	3.7 - 15.2	75
7601110	KS31	70 - 185	9.5 - 18.0	70 - 185	9.3 - 18.0	75
7601111	KS34	70 - 240	10.3 - 20.6	70 - 240	10.5 - 20.6	95
7601112	KS39	120 - 300	13.3 - 25.3	120 - 300	13.3 - 25.3	115
7601113	KS44	185 - 300	16.0 - 29.2	120 - 500	16.0 - 29.2	125

Connectors for copper cables on copper bars- KC series

General features

- copper alloy body
- bronze nut



Item code	Part number	Cable		Dimensions		
		Quantity	mm ²	m	d	h
7601150	KC15	1	4 - 6	1/4" - 20	12.7	15.8
7601151	K2C15	2	4 - 6	1/4" - 20	12.7	22.2
7601152	KC17	1	6 - 10	1/4" - 20	12.7	22.2
7601153	K2C17	2	6 - 10	1/4" - 20	12.7	25.4
7601154	KC20	1	6 - 16	5/16" - 18	15.8	22.2
7601155	K2C20	2	6 - 16	5/16" - 18	15.8	26.8
7601156	KC22	1	6 - 35	3/8" - 16	15.8	25.4
7601157	K2C22	2	6 - 35	3/8" - 16	15.8	31.8
7601158	KC23	1	10 - 50	3/8" - 16	15.8	25.4
7601159	K2C23	2	10 - 50	3/8" - 16	15.8	35.0
7601160	KC25	1	35 - 50	1/2" - 13	19.0	28.6
7601161	K2C25	2	35 - 50	1/2" - 13	19.0	41.3
7601162	KC26	1	35 - 70	1/2" - 13	19.0	35.0
7601163	K2C26	2	35 - 70	1/2" - 13	19.0	47.6
7601164	KC28	1	50 - 120	5/8" - 11	25.4	44.5
7601165	K2C28	2	50 - 120	5/8" - 11	25.4	57.2
7601166	KC31	1	50 - 185	5/8" - 11	25.4	57.2
7601167	K2C31	2	50 - 185	5/8" - 11	25.4	73.0
7601168	KC34	1	95 - 240	3/4" - 10	31.8	60.3
7601169	K2C34	2	95 - 240	3/4" - 10	31.8	82.6