



WEVER & DUCRÉ  
LIGHTING

# DEEPER 1.0 PAR16

152120W0

Project
Type
Notes
Quantity
Date

## GENERAL

Ceiling  
 Recessed  
 Signal White  
 IP20  
 Interior  
 480 lm  
 RAL 9003<sup>a</sup>

## LED

Lamp PAR16  
 PAR16  
 Socket GU10  
 max. 12 W  
 CRI 90

## OPTICAL

Wide Flood  
 Beam angle 48°

## PHYSICAL

Diameter 84 mm  
 Height 112 mm  
 0.15 kg


## ELECTRICAL

100 - 240 V  
 LED Inset 6.5 W  
 Class 2  
 Safety distance 0.3 m


## CUTOUT

Diameter 76-79 mm  
 Min. ceiling thickness 4 mm  
 Max. ceiling thickness 38 mm  
 Recessed depth 115 mm


<sup>a</sup> Color may deviate slightly due to production conditions.



Round ceiling recessed downlight made from die-cast aluminium; surface Signal White; powder coated; matt texture; RAL 9003; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 115 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC2; lamp not included;



## LIGHT DISTRIBUTION



[152120W0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# DEEPER 1.0 PAR16

152120W0

## CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	709	0.89
2	177	1.78
3	79	2.66
4	44	3.55
5	28	4.44

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50·58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50·58	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50·58	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50·58	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50·52	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50·52	9 0 5 2 2 7 S 4