

PRODUCT-DETAILS

E290-16-20/24

E290-16-20/24 Electromechanical latching relay



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | E290-16-20/24 |
| Code de produit | 2TAZ312000R2042 |
| EAN | 7612270939695 |
| Description courte | E290-16-20/24 Electromechanical latching relay |

Description longue

Latching relays are electromagnetically operated devices. The E290 range from ABB can be used to realise a simple, energy saving and efficient lighting control system. These devices are mainly used in private houses, factory premises and commercial and public buildings as well as in industrial plants. As a rule, latching relays controlled by means of impulse buttons are installed where it is necessary for lighting to be operated from at least three different places. Each time a command is initiated (by means of an impulse button), an electrical pulse is applied to the coil of the latching relay. The coil in the device is briefly energised and activated. That short pulse to the coil leads to the mechanical latch of the internal main contacts. The internal switching mechanism enables us to achieve a safe and reliable interlock (in the same way as a ballpoint pen). Each pulse that is sent to the magnetic coil system switches the device to its previous position where it is held mechanically until the next control pulse is received. The devices are designed for rated currents 16 and 32A. Through the combinable accessories the main modules can be used in nearly all market applications.

Technique

| | |
|------------------------|------------------------------------|
| Normes et standards | IEC/EN 60669-1 IEC/EN 60669-2-2 |
| Tension | 250 V AC |
| Tension d'alimentation | 21.6... 26.4 V AC |

| | |
|---|---|
| Tension assignée d'isolement (U_i) | 24 V AC 12 V DC |
| Rated Control Supply Voltage (U_g) | 24 V AC 12 V DC |
| Tension assignée de tenue aux chocs (U_{imp}) | 4 kV |
| Rated Control Circuit Voltage (U_c) | 24 V AC 12 V DC |
| Courant nominal (I_n) | 16 A |
| Current Rating, Main Switch | 16 A |
| Maximum Switching Current | 16 A |
| Fréquence assignée (f) | 50 Hz |
| Maximum Lamp Load | 3000 W Flourescent, Uncorrected Power Factor (cos. 0.5) 1800 W Flourescent, Corrected Power Factor (cos. 0.9): Serial 3000 W Flourescent, Corrected Power Factor (cos. 0.9): Parallel 2500 W Flourescent, Corrected Power Factor (cos. 0.9): Single 1800 W Flourescent, Corrected Power Factor (cos. 0.9): Double 2500 W |
| Power Loss | 0.64 W |
| Number of Contacts CO | 0 |
| Number of Contacts NC | 0 |
| Number of Contacts NO | 2 |
| Number of Main Contacts NC | 0 |
| Number of Main Contacts NO | 2 |
| Number of Auxiliary Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Niveau sonore dB (A) | (@distance 1 m) 60 dB |
| Couple de serrage | 1.2 - 1.5 N·m |
| Durée de Réponse | <3 ms |
| Impulse Duration | Minimum 50 ms |
| Contact Type | Normally Open (NO) |
| Type de montage | DIN rail |
| Options Provided | 2NO |
| Coil Consumption | Control Voltage V AC 24 V AC Average Pull-in Value 50 Hz 0.434 A Control Voltage V DC 12 V DC Average Pull-in Value 50 Hz 0.558 A |
| RAL Number | RAL 7035 - Gris clair |
| Couleur | Grey |
| Connecting Capacity | Solid 1 x 1 ... 10 mm ² Flexible 2 x 2.5 mm ² Flexible with Cable End 1 x 0.75 ... 6 mm ² Flexible with Cable Lug 1 x 0.75 ... 6 mm ² |

Environnement

| | |
|------------------------------|--|
| Température de l'air ambiant | Operation -25...+55 °C Storage -40...+70 °C |
|------------------------------|--|

| | |
|-----------------------------------|---|
| Statut RoHS | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| Informations environnementales | 2CCC441012D0202 |
| Climate Class Reference Standards | IEC 60068-2-2 - Deals with dry heat tests applicable both to heat-dissipating and non heat-dissipating specimens IEC 60068-2-30 - Determines the suitability of components, equipment or other articles for use, transportation and storage under conditions of high humidity - combined with cyclic temperature changes and, in general, producing condensation on the surface of the specimen. IEC 60068-2-1 - Deals with cold tests applicable to both non heat-dissipating and heat-dissipating specimens |

Technique UL/CSA

| | |
|-------------------------------------|------|
| Short-Circuit Current Rating (SCCR) | 3 kA |
|-------------------------------------|------|

Dimensions

| | |
|---|-------|
| Width in Number of Modular Spacings | 1 |
| Produit Largeur Net | 18 mm |
| Produit Hauteur Net | 85 mm |
| Produit Longueur Net | 62 mm |
| Poids net | 122 g |
| Produit Longueur Net | 62 mm |
| Profondeur d'encastrement (t ₂) | 68 mm |

Emballage

| | |
|-----------------------------|---------------|
| Emballage Niveau 1 Unités | box 10 pièce |
| Emballage Niveau 1 Largeur | 96 mm |
| Emballage Niveau 1 Hauteur | 82 mm |
| Emballage Niveau 1 Longueur | 185 mm |
| Emballage Niveau 1 Poids | 1296 g |
| Emballage Niveau 1 EAN | 7612270939695 |

Commande

| | |
|--------------------|------------|
| Quantité minimum | 10 pièce |
| Code douanier | 85364930 |
| E-Number (Finland) | 2712536 |
| E-Number (Sweden) | 4001188 |
| Pays d'origine | China (CN) |

Certificats et Déclarations (Numéro de document)

| | |
|-----------------------------------|-------------------|
| Déclaration de Conformité - CE | 2CCC005102D0201 |
| EAC Certificate | 9AKK107992A1778 |
| Informations environnementales | 2CCC441012D0202 |
| Instructions et manuels | 2CCC441005M0801 |
| Informations RoHS | 2CCC413008D0206 |
| VDE Certificate | VDE E29x_40040851 |

Popular Downloads

| | |
|---|-----------------|
| Fiche produit, informations techniques | 2CCC441020C0201 |
| Instructions et manuels | 2CCC441005M0801 |
| Schéma dimensionnel | 9AKK107992A6188 |

Classifications

| | |
|-----------------------------------|--|
| ETIM 7 | EC000188 - Latching relay |
| ETIM 8 | EC000188 - Latching relay |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| DEEE B2C / B2B | Business To Consumer |
| CN8 | 85362020 |
| eClass | V11.0 : 27142306 |
| Code de classification d'objet | K |

Accessories

| Identifiant | Description | Type | Quantity | Unit Of Measure |
|-----------------|--|-------------|----------|-----------------|
| 2CCA704300R0001 | E292-16-20 Main Contact Module | E292-16-20 | 10 | pièce |
| 2CCA704301R0001 | E292-16-11 Main Contact Module | E292-16-11 | 10 | pièce |
| 2CCA704302R0001 | E292-16-001 Main Contact Module | E292-16-001 | 10 | pièce |
| 2TAZ312001R2043 | E294/24 Central on-off Switching Module | E294/24 | 5 | pièce |
| 2TAZ312001R2013 | E294/230 Central on-off Switching Module | E294/230 | 5 | pièce |
| 2TAZ312005R1003 | E295-PS Permanent Signal Module | E295-PS | 10 | pièce |
| 2TAZ310002R1000 | E295-GM Group Module | E295-GM | 10 | pièce |
| 2TAZ310003R1000 | E296-CP Compensator | E296-CP | 10 | pièce |
| 2CCA704340R0001 | E299-11 Auxiliary contact 5A, 1NO+1NC | E299-11 | 10 | pièce |
| 2CCA704341R0001 | E299-20 Auxiliary contact | E299-20 | 10 | pièce |
| 2CCS500900R0181 | ZLS725 Spare parts | ZLS725 | 10 | pack |
| 2CCS400900R0091 | ZLS726 Spare parts | ZLS726 | 10 | pack |

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Latching Relays

