



**WEVER & DUCRÉ**  
LIGHTING

# DEEPER IP44 1.0 PAR16

152220W0

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling

Recessed

Signal White

IP44

Interior

420 lm

RAL 9003<sup>a</sup>

## LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 90

## OPTICAL

Wide Flood

Beam angle 48°

## PHYSICAL

Diameter 84 mm

Height 112 mm

0.15 kg

## ELECTRICAL

100 - 240 V

LED Inset 6.5 W

Class 2

Safety distance 0.3 m

## CUTOUT

Diameter 76-79 mm

Min. ceiling thickness 4 mm

Max. ceiling thickness 38 mm


Recessed depth 115 mm

<sup>a</sup> Color may deviate slightly due to production conditions.




IP44  $\pm 0,3 \rightarrow$

Round ceiling recessed downlight made from die-cast aluminium; surface Signal White; powder coated; matt texture; RAL 9003; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 115 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection from below IP44; from above IP20; PC2; lamp not included;



## LIGHT DISTRIBUTION



[152220W0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# DEEPER IP44 1.0 PAR16

152220W0

## CONE DIAGRAM

wide flood 48°

h (m)	EO <sup>3</sup> (lx)	ø (m)
1	624	0.89
2	156	1.78
3	69	2.66
4	39	3.55
5	25	4.44

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50·58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50·58	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50·58	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50·58	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50·52	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50·52	9 0 5 2 2 7 S 4