



WEVER & DUCRÉ  
LIGHTING

# DEEP 1.0 PAR16

112120B0C

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling

Recessed

Jet Black

IP20

Interior

445 lm

RAL 9005<sup>a</sup>

## LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 90

## OPTICAL

Wide Flood

Beam angle 48°

## PHYSICAL

Diameter 84 mm

Height 102 mm

0.29 kg

blade springs

## ELECTRICAL

100 - 240 V

LED Inset 6.5 W

Class 2

Safety distance 0.3 m



## CUTOUT

Diameter 76-79 mm


Min. ceiling thickness 10 mm

Recessed depth 105 mm

<sup>a</sup> Color may deviate slightly due to production conditions.



## LIGHT DISTRIBUTION



[112120B0C] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# DEEP 1.0 PAR16

112120B0C

## CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	623	0.89
2	156	1.78
3	69	2.67
4	39	3.56
5	25	4.45

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50·58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50·58	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50·58	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50·58	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50·52	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50·52	9 0 5 2 2 7 S 4