



WEVER & DUCRÉ
LIGHTING

SQUBE

on base #3 PAR16

144620B0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Jet Black

IP20

Interior

1370^a to 1390^b lm

RAL 9005^c

LED

Lamp 3 x PAR16

PAR16

Socket GU10

max. 12 W

CRI \geq 80

OPTICAL

Beam angle 47°

PHYSICAL

Length 360 mm

Width 55 mm

Height 125 mm

0.93 kg

Tilt min 90°

Tilt max 90°

Rotation 355°

ELECTRICAL

100 - 240 V

Total connected power 19.8^b to 20^a W


Class 1

Safety distance 0.3 m


^a LED 3000K CRI 80 white

^b LED 2700K CRI 80 white


^c Color may deviate slightly due to production conditions.



Ceiling surface spotlight made from die-cast aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 90° tiltable; degree of protection IP20; PC1; lamp not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

SQUBE

on base #3 PAR16

144620B0

CONE DIAGRAM

LED 2700K CRI ≥ 80 White

h (m)	EO° (lx)	ø (m)
1	1940	0.88
2	480	1.75
3	220	2.63
4	120	3.50
5	80	4.38

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50-58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50-58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50-58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50-52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50-52	9 0 5 2 2 7 S 4