



**WEVER & DUCRÉ**  
LIGHTING

# SQUBE

## on base #3 PAR16

144620W0

Project

Type

Notes

Quantity

Date

### GENERAL

Ceiling

Surface

Signal White

IP20

Interior

1370<sup>a</sup> to 1390<sup>b</sup> lm

RAL 9003<sup>c</sup>

### LED

Lamp 3 x PAR16

PAR16

Socket GU10

max. 12 W

CRI 80

### OPTICAL

Beam angle 47°

### PHYSICAL

Length 360 mm

Width 55 mm

Height 125 mm

0.93 kg

Tilt min 90°

Tilt max 90°

Rotation 355°

### ELECTRICAL

100 - 240 V

Total connected power 19.8<sup>b</sup> to 20<sup>a</sup> W


Class 1

Safety distance 0.3 m


<sup>a</sup> LED 3000K CRI 80 white

<sup>b</sup> LED 2700K CRI 80 white


<sup>c</sup> Color may deviate slightly due to production conditions.



Ceiling surface spotlight made from die-cast aluminium; surface Signal White; powder coated; matt texture; RAL 9003; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; 355° rotatable and 90° tiltable; degree of protection IP20; PC1; lamp not included;



### LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# SQUBE

## on base #3 PAR16

144620W0

### CONE DIAGRAM

LED 2700K CRI  $\geq 80$  White

h (m)	EO° (lx)	ø (m)
1	1940	0.88
2	480	1.75
3	220	2.63
4	120	3.50
5	80	4.38

### LAMPS

#### PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50-58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50-58	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50-58	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50-58	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50-52	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50-52	9 0 5 2 2 7 S 4