



WEVER & DUCRÉ
LIGHTING

COSTA 2.0

8652860B9

Project _____

Type _____

Notes _____

Quantity _____

Date _____

GENERAL

Floor _____

Standing _____

White LLDPE + Black _____

IP65 _____

Exterior _____

130 lm _____

LED

2200 K - 4000 K _____

3-step binning _____

PHYSICAL

Diameter 280 mm _____

Height 350 mm _____


1.1 kg _____

ELECTRICAL

220 - 240 V _____

Total connected power 3 W _____

Class 3 _____





WEVER & DUCRÉ
LIGHTING

COSTA 2.0

8652860B9

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.93	0.89	0.86	0.82
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Rope 2.0

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
COSTA 2.0	Black	∅280·285	9 0 0 5 7 1 9 0
COSTA 2.0	Traffic Orange	∅280·285	9 0 0 5 7 1 9 1
COSTA 2.0	Colza Yellow	∅280·285	9 0 0 5 7 1 9 2
COSTA 2.0	Water Blue	∅280·285	9 0 0 5 7 1 9 3

Cage 2.1

TYPE	COLOUR	ORDERCODE
COSTA 2.0	Black	9 0 0 5 7 1 8 0
COSTA 2.0	Traffic Orange	9 0 0 5 7 1 8 1
COSTA 2.0	Colza Yellow	9 0 0 5 7 1 8 2
COSTA 2.0	Water Blue	9 0 0 5 7 1 8 3

MOUNTING

POLE

TYPE	Ø·H (MM)	ORDERCODE
COSTA	450·∅350-1800	9 0 0 5 6 0 0 1