

PRODUCT-DETAILS

# UD/S4.210.2.1

## UD/S4.210.2.1 LED-Dim actuator 4x210W



### Informations générales

Extension du type de produit	UD/S4.210.2.1
Code de produit	2CKA006197A0047
EAN	4011395251867
Description courte	UD/S4.210.2.1 LED-Dim actuator 4x210W

Description longue	<p>Multichannel universal dimming actuator optimised for dimming retrofit LED lamps (LEDi). Also suitable for dimming incandescent lamps, low-voltage halogen lights with conventional or electronic transformers, 230 V halogen lamps and dimmable energy-saving halogen lamps. Automatic load detection (can be deactivated). Separate N-connection per channel. Parallel connection of the outputs possible to increase the output power. Outputs can be connected in parallel in any configuration. Minimum load: 2 W. Manual operation on device also possible without bus voltage or in an unprogrammed status. Programming of the device also possible without applied 230V supply voltage. Extensive test and diagnosis functions for the i-Bus tool. Fast parameter setting in ETS using copyable channel templates. With integrated bus coupler. Nominal power at 230 V~ mains voltage: 230 V~ incandescent and halogen lamps: 4 x 210 W/VA to 1 x 600 W/VA. Dimmable 230 V~ LEDi: 4 x 210 W/VA to 1 x 600 W/VA in trailing edge control, 4 x 80 W/VA to 1 x 200 W/VA in leading edge control. Inductive L-transformers with LED/low-voltage halogen lamp: 4 x 210 W/VA to 1 x 600 W/VA. Electronic C-transformers with LED/low-voltage halogen lamp: 4 x 210 W/VA to 1 x 600 W/VA. Electronic LC-transformers with LED/low-voltage halogen lamp: 4 x 80 W/VA to 1 x 200 W/VA.</p>
--------------------	--

### Commande

EAN	4011395251867
Code douanier	85389091

Quantité minimum	1 pièce
E-Number (Finland)	2814591
E-Number (Sweden)	1739490

## Dimensions

Poids net	283 g
-----------	-------

## Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 EAN	4011395251867
Emballage Niveau 1 Longueur	150 mm
Emballage Niveau 1 Hauteur	96 mm
Emballage Niveau 1 Largeur	125 mm
Emballage Niveau 1 Poids	0.283 kg

## Technique

Température de l'air ambiant	Operation -5 ... +45 °C
Compatible Bus Systems	KNX (TP)
Indice de protection	IP20
Type de montage	DIN-Rail
Width in Number of Modular Spacings	80

## Certificats et Déclarations (Numéro de document)

Fiche produit, informations techniques	No document needed
Déclaration de Conformité - CE	2CKA100000E2617
Instructions et manuels	2CKA000073B9628
Informations RoHS	9AKK104295D8727

## Environnement

Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

## Classifications

ETIM 7	EC001094 - Dimming actuator for bus system
ETIM 8	EC001094 - Dimming actuator for bus system
eClass	V11.0 : 27143123

---

## Catégories

---

Produits basse tension → Home and Building Automation → KNX → Lighting Control → Universal Dim Actuators

