
3M

Volition[™] Advanced Patching Solutions 19" RJ45 Patch Panels



Part of the end-to-end structured copper and fibre cabling Volition™ range, 3M™ Volition™ Advanced Patching Solutions are designed to help network and data centre operators implement reliable, easy to use and easy to maintain structured cabling systems to effectively support all types of networks.

The Volition $^{\text{TM}}$ Advanced Patching Solutions 19" RJ45 Patch Panels are available with 16 or 24 ports and are compatible with all Volition $^{\text{TM}}$ Keystone RJ45 Jacks, from Category 5e to Category 6_A.

The new, attractive design, in dark grey colour with black trim, in conjunction with the integrated cable and patch cord management systems and with the common set of accessories, provides a coherent and homogeneous coverage for all network applications.

Features

- Part of a new, complete range of 19" Patch Panels.
- New design.
- RJ45 keystone panels.
- New fixing system without cage nuts.
- Automatic grounding system.
- Rear cable management system.
- Three way RJ45 port identification.
- Wide range of patch cord management accessories

Benefits

- Complete set of 1U panels for copper, fibre (available in 2013), telephony (available in 2013) and cable management.
- Panels are dark grey and accessories for cable fixing and cable management are black.
- Modern aesthetic look integrates well with active components for a homogeneous and coherent total appearance.
- Compatible with Volition™ RJ45 Jacks, Category 6_A, 6A Permanent Link, 6 and 5e.
- The 'easy fixing' system uses two screws integrated in the panel instead of separate cage nuts and screws, providing significant savings in terms of installation time.
- After fixing, the screws are covered by a cap, giving a neat and uniform appearance to the panels in the rack.
- Automatic connection to ground when the jack is inserted in the panel and the panel is fixed onto the rack. An additional grounding kit (ref. VOLSPKG) is available for applications with painted 19" rails.
- The integrated cable management system secures the cables on the back of the RJ45 panels, making fixing with cable ties (not included) optional.
- Port numbering is visible on the front and inside the panel.
- Large area on the front (full width of the panel) for adhesive labels.
- Coloured identifiers (with or without label holder) for RJ45 ports.
- Front patch cord management with 1U panels equipped with plastic rings (75mm or 100mm depth).
- Side patch cord management with plastic rings (50mm or 75mm depth) that are directly fixed on the panel.



Technical Specifications

- 19" patch panel compatible with 3M RJ45 keystone jacks Category 6A, 6A Permanent Link, 6 and 5e.
- Dust protection on panel ports when equipped with RJ45 jacks.
- Integrated cable support and fixing system.
- Port numbering and labelling according to EIA/TIA 606 and ISO/IEC/TR 14763-2-1.
- 1U version available in 16 or 24 ports.
- Equipped with two plastic covers to hide the fixing screws.
- Individual grounding of each port (when equipped with FTP or STP RJ45 jacks).
- Compatible with 3M RJ45 Splitters.

| Ordering Information | | Ref. No. |
|---|---|-----------|
| *************************************** | 19" patch panel, 24 ports, 1U For 24 RJ45 keystone jacks Dimensions (WxHxD): 482.6 x 43.6 x 122.6 mm | VOLSPK24 |
| | 19" patch panel, 16 ports, 1U For 16 RJ45 keystone jacks Dimensions (WxHxD): 482.6 x 43.6 x 122.6 mm | VOLSPK16 |
| Accessories | | Ref. No. |
| 000 | Patch cord management panels, 1U 4 rings, 100 mm depth Dimensions (WxHxD): 482.6 x 43.6 x 120 mm | VOLSPM100 |
| | 4 rings, 75 mm depth Dimensions (WxHxD): 482.6 x 43.6 x 95 mm | VOLSPM75 |
| | Patch cord management panel with organizer Dimensions (WxHxD): 482.6 x 43.6 x 243.6 mm | VOLSPMW |
| | Cable management rings Set of 2 rings, 75 mm Dimensions (WxHxD): 17.6 x 43.6 x 75.3 mm | VOLSPR75 |
| | Set of 2 rings, 50 mm Dimensions (WxHxD): 17.6 x 43.6 x 50.3 mm | VOLSPR50 |
| | Grounding kit Cable with two fixing elements Dimensions (length): 200 mm | VOLSPKG |



19" blanking panel, 1U

VOLSPB

Dimensions (WxHxD): 482.6 x 43.6 x 35.1 mm



Coloured identifiers, set of 8

Blue **VOLPCCB** Yellow **VOLPCCY** Red **VOLPCCR** Green **VOLPCCG**



Coloured identifiers, set of 8, with label holder

Blue **VOLPECB VOLPECY** Yellow Red **VOLPECR** Green **VOLPECG**

Important Notice

The details contained in this literature have been carefully prepared from information available to 3M at the time of its production. However, it is not intended to be relied upon for purposes of product specification and you should contact your sales representative if specification details are required. Because of the wide variety of processes and conditions in which these products may be used, the user should first carry out tests to determine the suitability of the products for the particular use intended. All questions of warranty and liability relating to 3M products are governed by the selling 3M subsidiary's Terms of Sale subject where applicable to the prevailing law. 3M is trademark of the 3M company. SID is a trademark of Quante AG.



3M Telecommunications

Europe, Middle East & Africa c/o 3M Deutschland GmbH Carl-Schurz-Straße 1 41453 Neuss · Germany Tel.: ++49 (0)2131 / 14-5999 Fax: ++49 (0)2131 / 14-5998 Internet: www.3MTelecommunications.com