

PRODUCT-DETAILS

ESB40-40N-06

ESB40-40N-06 Installation Contactor



Informations générales

Extension du type de produit	ESB40-40N-06
Code de produit	1SAE341111R0640
EAN	4013614518515
Description courte	ESB40-40N-06 Installation Contactor
Description longue	<p>The ESB40..N installation contactors are used to control single and three-phase loads up to 40 A and can be operated by AC or DC.</p> <p>These contactors are made for use in household applications as well as in industrial environments.</p> <p>The following benefits are provided:</p> <p>Hum-free operation, low power consumption and integrated overvoltage protection.</p> <p>Various contact combinations and accessories are available.</p>

Commande

Emballage Niveau 1 EAN	4013614524820
Quantité minimum	1 pièce
Code douanier	85365080

Popular Downloads

Instructions et manuels	2CDC103043M6801
-------------------------	-----------------

Dimensions

Produit Largeur Net	54 mm
Produit Hauteur Net	85 mm
Produit Longueur Net	65 mm
Poids net	0.405 kg

Technique

Tension	Circuit principal 220 V DC Circuit principal 400 V AC
Rated Control Circuit Voltage (U_c)	230 V
Fréquence assignée (f)	Circuit de commande 400 Hz Circuit de commande 50 Hz Circuit de commande 60 Hz Circuit de commande DC Circuit principal 50 Hz Circuit principal 60 Hz Circuit principal DC
Courant assignée d'emploi AC-1 (I_e)	(NO) 40 A
Courant assignée d'emploi AC-3 (I_e)	(230 V) Single Phase, NO 22 A (400 V) Three Phase, NO 22 A
Puissance assignée d'emploi AC-1 (P_e)	(230 V) Single Phase, NO 9.2 kW (400 V) Three Phase, NO 27.7 kW
Puissance assignée d'emploi AC-3 (P_e)	(230 V) Single Phase, NO 3.7 kW (400 V) Three Phase, NO 11 kW
Rated Operational Current AC-7a (I_e)	(NO) 40 A
Rated Operational Power AC-7a (P_e)	(230 V) Single Phase, NO 9.2 kW (400 V) Three Phase, NO 27.7 kW
Rated Operational Current AC-7b (I_e)	(230 V) Single Phase, NO 22 A (400 V) Three Phase, NO 22 A
Rated Operational Power AC-7b (P_e)	(230 V) Single Phase, NO 3.7 kW (400 V) Three Phase, NO 11 kW
Recommended Screw Driver	Circuit de commande Pozidriv 1 Circuit principal Pozidriv 2
Tension assignée de tenue aux chocs (U_{imp})	6 kV
Tension assignée d'isolement (U_i)	500 V
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 1.5 ... 16 mm ² Flexible with Ferrule 2x 1.5 ... 10 mm ² Flexible with Insulated Ferrule 1x 1.5 ... 16 mm ² Flexible with Insulated Ferrule 2x 1.5 ... 10 mm ² Flexible 1x 1.5 ... 16 mm ² Flexible 2x 1.5 ... 10 mm ² Rigid 1x 1.5 ... 25 mm ² Rigid 2x 1.5 ... 10 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1 mm ² Flexible 1x 1 ... 4.0 mm ² Flexible 2x 1 ... 2.5 mm ²

	Rigid 1x 1 ... 4 mm ² Rigid 2x 1 ... 2.5 mm ²
Couple de serrage	Control Circuit 0.9 N·m Main Circuit 2.5 N·m
Wire Stripping Length	Control Circuit 7 mm Main Circuit 13 mm
Indice de protection	IP20
Electrical Durability	AC-1 (NO) 150000 cycle AC-3 (NO) 150000 cycle AC-7a (NO) 150000 cycle AC-7b (NO) 150000 cycle
Durabilité mecanique	1000000 cycle
Nombre de pôles	4
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Main Contacts NC	0
Number of Main Contacts NO	4
Width in Number of Modular Spacings	3
Degré de pollution	3
Normes et standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 61095 UL 60947-1 UL 60947-4-1

Technique UL/CSA

Maximum Operating Voltage UL/CSA	Circuit principal 480 V AC
Puissance nominale UL/CSA	(220 ... 240 V AC) Single Phase, NO 3 Hp (220 ... 240 V AC) Three Phase, NO 7.5 Hp (440 ... 480 V AC) Single Phase, NO 7.5 Hp (440 ... 480 V AC) Three Phase, NO 15 Hp
Connecting Capacity Main Circuit UL/CSA	Solid 16-4 AWG Stranded 16-4 AWG
Connecting Capacity Control Circuit UL/CSA	Solid 16-10 AWG Stranded 16-10 AWG
Tightening Torque UL/CSA	Control Circuit 8 in·lb Main Circuit 20 in·lb

Environnement

Température de l'air ambiant	Operation -25 ... +55 °C Storage -40 ... +80 °C
Altitude de fonctionnement maximale autorisée	2000 m
Résistance aux chocs selon CEI 60068-2-27	11 ms Pulse 15g
Statut RoHS	Following EU Directive 2011/65/EU

Certificats et Déclarations (Numéro de document)

Certificat ABS	1SAA920000-0101
CB Certificate	1SAA920005-2001
CQC Certificate	CQC2017010304993562 CQC2017010304993563
Certificat ecULus	cUL_E191658
Declaration of Conformity - CCC	2020980304001310 2020980304001313
Déclaration de Conformité - CE	1SAD938506-0302
Declaration of Conformity - UKCA	1SAD938501-1302
Certificat DNV	1SAA920000-0306
EAC Certificate	1SAA920001-2702
Informations environnementales	1SAC200064H0009
Instructions et manuels	2CDC103043M6801
Certificat NF	1SAA920001-1202
Certificat RINA	1SAA920000-0801
Certificat RMRS	1SAA920000-0705
Informations RoHS	1SAD938506-0302

Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 Largeur	92 mm
Emballage Niveau 1 Hauteur	69.5 mm
Emballage Niveau 1 Longueur	57 mm
Emballage Niveau 1 Poids	0.405 kg
Emballage Niveau 1 EAN	4013614524820
Emballage Niveau 2 Unités	34 pièce
Emballage Niveau 2 Largeur	280 mm
Emballage Niveau 2 Hauteur	210 mm
Emballage Niveau 2 Longueur	395 mm
Emballage Niveau 2 Poids	14.3 kg
Emballage Niveau 2 EAN	4013614539213

Classifications

Code de classification d'objet	Q
ETIM 5	EC001653 - Installation contactor for distribution board
ETIM 6	EC001653 - contacteur d'installation pour montage sur rail

ETIM 7	EC001653 - Installation contactor for distribution board
eClass	V11.0 : 27142308
UNSPSC	39121529
Code de catégorie granulaire IDEA (IGCC)	4759 >> Installation contactor for distribution board
E-Number (Finland)	3707581
E-Number (Sweden)	3210571
ETIM 8	EC001653 - Installation contactor for distribution board

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Contacteurs modulaires

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Contacteurs → Contacteurs modulaires

