



WEVER & DUCRÉ  
LIGHTING

# BOX mini 1.0

258120B0

Project

Type

Notes

Quantity

Date

## GENERAL

Ceiling

Surface

Jet Black

IP20

Interior

400<sup>a</sup> to 405<sup>b</sup> lm

RAL 9005<sup>c</sup>

## LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 80

## OPTICAL

Beam angle 48°

## PHYSICAL

Length 70 mm

Width 70 mm

Height 82 mm

0.16 kg

## ELECTRICAL

100 - 240 V

Total connected power 6.6<sup>b</sup> to 6.7<sup>a</sup> W

Class 1

Safety distance 0.3 m


<sup>a</sup> LED 3000K CRI 80 white

<sup>b</sup> LED 2700K CRI 80 white


<sup>c</sup> Color may deviate slightly due to production conditions.



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; optional inner reflector available; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; UGR 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° 1500 cd/m<sup>2</sup>; lamp not included;



## LIGHT DISTRIBUTION



[258120B0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# BOX mini 1.0

258120B0

## CONE DIAGRAM

LED 3000K CRI ≥ 80% white

h (m)	EO° (lx)	ø (m)
1	602	0.90
2	151	1.80
3	67	2.70
4	38	3.60
5	24	4.50

## OPTICAL

### Inner Reflector

TYPE	COLOUR	ORDERCODE
BOX mini   max. 10W	Black	9 0 0 1 9 9 B 1
BOX mini   max. 10W	Gold	9 0 0 1 9 9 G 1
BOX mini   max. 10W	Bronze	9 0 0 1 9 9 Q 1
BOX mini   max. 10W	White	9 0 0 1 9 9 W 1

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø-H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50-58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50-58	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50-58	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50-58	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50-52	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50-52	9 0 5 2 2 7 S 4