

# Smappee Power Box



- Works with almost any electricity network worldwide.
- Energy metering functionalities.
- You can measure up to 28 loads.
- Provides power to the entire system.

The Power Box is the compact and robust heart of the Smappee Infinity monitoring system. It's compatible with almost any electricity network worldwide and is DIN-rail mountable. It measures the line voltage of the connected phases, collects the currents from the CT sensors and calculates power, active energy, reactive energy and other energy and power quality data. It also provides power to all components.

- **Dimensions:** 55 × 55 × 26,6 mm [2.17 × 2.17 × 1.05 inches]
- **Weight:** 44 g (1.55 oz)
- **Operating temperature:** -25 °C to 75 °C (-13 °F to 167 °F)
- **Storage temperature:** -25 °C to 90 °C (-13 °F to 194 °F)
- **Relative humidity:** 0 % - 95 %, non-condensing
- **Operating altitude:** 0 - 2,000 m [0 - 6,562 feet]
- **Product certification:** CE, FCC, CSGSus (UL 61010-1), RCM
- **EMC:** IEC 61326-1, FCC 47 part 15
- **Safety:** IEC 61010-1:2010/COR1:2011  
Complies with UL 61010-1 and CAN/CSA-C22.2 No. 61010-1-12
- **Impact rating (IEC 62262):** 1k 06 (Impact Energy: 1J)
- **IP rating (IEC 60529):** IP X0
- **Power supply input:** 90 - 264 V AC
- **Power consumption:** 8 W max
- **Voltage measurement inputs:** L1, L2, L3, N
- **Topology and maximum nominal ranges:**
  - Single phase - 1-: 240 Vrms
  - Split phase - 2-: 120/240 Vrms
  - 3 phase (3 wires) - 3-: 240 Vrms
  - 3 phase (4 wires) - 3-: 240/415 Vrms
  - 3 phase (4 wires) - 3-: 277/480 Vrms
- **Frequency:** 50/60 Hz
- **Intended environment conditions:** Pollution degree 2
- **Overvoltage conditions:** overvoltage category II
- **Connectivity:**
  - Smappee Bus A
  - Smappee Bus B
- **Accessories included:**
  - DIN mounting plate
  - Power cable 90 cm open-ended (35.43 inches) or 180 cm open-ended (70.87 inches) in case of L1-VAC-US
  - Bus termination plug