



Single Phase

7.4

 kW/32 A

SCharger-7KS-S0

Three Phase

22

 kW/32 A

SCharger-22KT-S0



PV Power Preferred ¹

Power Your Car with Solar
Make EV Even Greener



Automatic Phase Switch ²

Automatic Switch between 1 Phase and 3 Phase
More Usable Green Power



3 Ways Authentication

Bluetooth, RFID and APP
Avoid Accidental Charging



Dynamic Charging Power

Automatic Detection and Adjustment
No Worry about Overload



All on a Single APP

Full Control Through One APP
for All PV + ESS + Charger



3-Step Installation

Fast Installation in 16 Minutes
Wiring-free Maintenance

Smart Charger
Technical Specifications

| Technical Specification | SCharger-7KS-S0 | SCharger-22KT-S0 |
|---|---|--|
| Inputs and Outputs | | |
| Charge power (configurable) | 1.4 kW to 7.4 kW | 1.4 kW ³ to 22 kW |
| Nominal voltage | 230 V (1-phase) ± 20% | 400 V (3-phase) ± 20% |
| Nominal current (configurable) | 6–32 A (1-phase) | 6–32 A (3-phase or 1-phase) |
| Nominal frequency | 50 Hz/60 Hz ± 1 Hz | |
| Vehicle connection | Type 2 socket | |
| Cable width | Up to 10 mm ² | |
| Network types | TN, TT, IT | TN, TT |
| User Interface & Communications | | |
| Protocol | Modbus TCP | |
| Communication | Wi-Fi/Ethernet | |
| Charger status information | WRGB LED, App | |
| Authentication | RFID (ISO-14443-A), App, Bluetooth | |
| Remote control & monitoring | App | |
| Working mode | Normal Charge Scheduled Charge PV Power Preferred | |
| Protection | | |
| Cable protection | Cable E-Lock via App | |
| Residual current protection (RCD) | Type A(30mA) + DC 6 mA integrated (IEC 62955 & IEC 61008-1) | |
| Fire Class | UL94 | |
| Overcurrent protection | IEC 61851-1 | |
| Over-temperature protection | Yes | |
| Surge protection | CAT II | |
| General Specifications | | |
| Operating temperature range | -35°C to +45°C | -35°C to +40°C @ 32A -35°C to +50°C @ 16A |
| Application environment | Outdoor/Indoor | |
| Storage temperature | -40°C to +70°C | |
| Relative humidity | 5% RH–95% RH | |
| Altitude | ≤ 2000 m (derating between 2000–4000m) | |
| Dimensions (H x W x D) | 335 mm x 180 mm x 145 mm | |
| Weight | 3 kg | 3.1 kg |
| Installation mode | Wall-mounted | |
| IP rating | IP54 | |
| Impact protection level | IK10 | |
| Standby self-consumption | < 6 W | |
| Standards Compliance (More Available Upon Request) | | |
| Standard | EN 61851-1 2019, IEC 62955:2018, IEC 61008-1 2010, IEC/EN 62196-1 | |
| Others | | |
| Accessories | RFID Card * 2 | |

*1 Currently available for free trial and will be notified 30 days in advance, when the function enters the charging phase

*2 Available in PV Power Preferred Mode



*3 1.4 kW for 1-Phase charge and 4.2 kW for 3-Phase charge



Copyright © Huawei Technologies Co., Ltd. 2022. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademark Notice

 , HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd. Other trademarks, product, service and company names mentioned are the property of their respective owners.

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES Dusseldorf GmbH

Südwestpark 37,90449 Nürnberg, Deutschland
Hotline.: +80 03 38 88 888
Email: eu_inverter_support@huawei.com

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base Bantian Longgang Shenzhen 518129, P.R. China
Tel.: 400-822-9999
Version No.: 05-(202201222)
solar.huawei.com

