



# Portable Worklight LED 3.7V 3000mAh Rechargeable Li- Battery 500lm 6000K IPX4 IK07

## Basic data:

ID	0006940011
GTIN	7630268418366



## Features:

- Material: aluminium housing and plastic holder
- Battery: 3.7V 3,000mAh
- Modes: COB Low - COB High - Samsung LED ON - OFF
- 1. Long press the switch to enter the docking mode, and the indicator will blink.
- 2. When an electronic device is successfully connected to the worklight, the indicator will be on for a long time.
- 3. When the pairing between the electronic devices and the worklight is canceled, the indicator will automatically turn to blink, then the work light can be paired with a new electronic device.
- 4. Automatically disconnect the device, and the product shuts down automatically.
- Max output: 500lm
- Run time: 3h-14h-6h (COB)
- Recharging time: 4.5h (USB charging port)
- Speaker
- Signal distance: 8m
- USB-C port + 1pc cable included
- USB input: 5V 1A
- With magnet & hook on back
- With power indicator
- IPX4, IK07

## Technical data:

Rechargeable:	Yes
Built-in charging circuit:	Yes
Main lamp:	LED not exchangeable
Auxiliary lamp:	LED not exchangeable
With light source:	Yes
Housing material:	Aluminium
Housing colour:	Multi-coloured
Voltage type:	DC
Suitable for emergency lighting:	Yes
Nominal voltage:	3.7 V
Degree of protection (IP):	IPX4
Protection class:	III
Rated luminous flux according to IEC 62722-2-1:	500 lm
Colour temperature:	6000 K
Width:	27 mm
Height/depth:	164 mm
Length:	66 mm
Type of wiring:	Ending